CHAPTER 5

REFERENCES CITED

5.0 REFERENCES CITED

- A. Strauss-Weider, Inc. and Center for Urban Policy Research (CUPR) at Rutgers University. 2000. Port Economic Impact Kit, Version 1.1. Prepared for U.S. Department of Transportation, Maritime Administration. December.
- Abbott, R.R. 1973. Acoustic Sensitivity of Salmonids. PhD dissertation. University of Washington, College of Fisheries, Seattle.
- Alaska Coastal Management Program (ACMP). 1981. Areas Meriting Special Attention Enforceable Policies. Office of Project Management and Permitting, Department of Natural Resources. Http://www.alaskacoast.state.ak.us/Explore/amsas/Anchorageamsas.pdf (accessed 4 May 2004). 22 June.
- Alaska Department of Environmental Conservation (ADEC) and U.S. Defense Energy Support Center (DESC). 2003. Record of Decision for Cleanup, Defense Fuel Support Point-Anchorage. ADEC Database Record Key 1988-21-X1-119-01. 18 February.
- Alaska Department of Fish and Game (ADFG). 2004a. Fish Distribution Database Interactive Mapping. Http://www.sf.adfg.state.ak.us/sarr/FishDistrib/FDD_ims.cfm.
 2004b. Commercial Fishing Seasons in Alaska: Cook Inlet. Http://www.cf.adfg.state.ak.us/geninfo/pubs/seasons/season_1.pdf (accessed 10 February 2004).
 2004c. Fish Distribution Database Fish profiles. Http://www.sf.adfg.state.ak.us/sarr/FishDistrib/FDD_fishprofiles.cfm. (accessed 10 February 2004).
 2004d. Upper Cook Inlet Salmon Fisheries: Historical Information. Http://www.cf.adfg.state.ak.us/region2/ucihome.php. (accessed 10 February 2004).
 2004e. Sport Fish Hatchery Program: Fort Richardson Hatchery and Elmendorf Hatchery. Http://www.sf.adfg.state.ak.us/statewide/hatchery/Hatchery.cfm. (accessed 17 February 2004).
 2004f. Coho, Chum Salmon: Wildlife Notebook Series.

Http://www.adfg.state.ak.us/pubs/notebook/fish//coho.php (accessed 21 October 2004).

_____. 2003. Upper Cook Inlet Commercial Fisheries Annual Management Report, 2002. Regional

Information Report No. 2A03-14. Commercial Fisheries Division. April.

•	2002. Sport Fish Division. Http://www.sf.adfg.state.ak.us/statewide/sf_home.cfm. (accessed 18 May 2004).
·	1991. Anchorage Coastal Wildlife Refuge Management Plan. February.
Alaska	Department of Natural Resources (ADNR). 2004. Data List of Borrow Sources. Division of Mining and Water. June.
·	1999. Cook Inlet Area Wide 1999 Oil and Gas Lease Sale, Final Finding of the Director. Chapter Three: Habitat, Fish and Wildlife. Division of Oil and Gas. Http://www.dog.dnr.state.ak.us/oil/products/publications/cookinlet/cia1999 final_finding/cifinding_contents.htm (accessed 17 February 2004). 20 January.
Alaska	Division of Governmental Coordination (ADGC). 2003. Municipality of Anchorage Coastal Management Program Enforceable Policies. Http://www.alaskacoast.state.ak.us/.
Alaska	Natural Heritage Program (ANHP). 2004. Personal communication from Julia Lenz, Research Technician, University of Alaska, Environmental and Natural Resources Institute. Regarding information on threatened, endangered, or sensitive species within a three-mile radius of the Port of Anchorage. 16 April.
·	2003. Vascular Plant Tracking List for Alaska. 4 April.
Alaska	Office of History and Archaeology (AOHA). 2004. Personal Communication from Joan Dale, Archaeologist. Regarding information on the eligibility of the proposed Brown's Point Historic District.
·	2003a. ANC-01337 Tak'at Dena'ina Fish Camp.
·	2003b. ANC-01302 Anchorage Terminal of the Whittier-Anchorage Pipeline.
·	1992. ANC-00706 G.W. Palmer Warehouse.
·	1983. ANC-00306 Wireless Station (The Alaska Core Library).
·•	1974a. ANC-00046 349 West Harvard Avenue (AEC Cottage #7).
•	1974b. ANC-00047 300.5 East Cook Avenue (Quonset Hut).

Port of Anchorage Marine Terminal Redevelopment Environmental Assessment ... 1974c. ANC-00048 Civil Residential Dwelling (786 Delaney Street). . 1974d. ANC-01205 Civil Works Residential Dwelling (800 Delaney Street). . 1974e. ANC-00049 Federal Buildings. Alaska Regional Response Team (ARRT). 1997. Cook Inlet Subarea Contingency Plan for Oil and Hazardous Substance Spills and Releases: A Subarea Plan of the Unified Plan for the State of Alaska. Http://www.akrrt.org/Clplan/Cltoc.shtml. July. Alaska Unified Response Team (AURT). 1999. Unified Plan Volume II. Http://www.akrrt.org/UnifiedPlan/index.shtml. September. Alaska Volcano Observatory (AVO). 2004. Anchorage Community Overview. Http://www.avo.alaska.edu/avo4/town/ancho.htm. March. Anchorage Audubon Society (AAS). 2004. Important Bird Areas of Cook Inlet, AK-CI-001 Anchorage Coastal Important Bird Area, Draft. 18 October. 1993. Birds of Anchorage (Knik River to Portage): A Checklist. October. Anchorage Metropolitan Area Transportation Study (AMATS). 2001. Freight Mobility Study for the Anchorage Metropolitan Area. Municipality of Anchorage. June. Betke, K., M. Schultz-von Glahn, and R. Matuschek. 2004. Underwater Noise Emissions from Offshore Wind Turbines. ITAP – Institut für technische und angewandte Physik GmbH. Blackwell, S.B. and C.R. Greene, Jr. 2002. Acoustic Measurements in Cook Inlet, Alaska, during August 2001. Prepared for NMFS, Protected Resources Division. 12 August. California-Nevada Super Speed Train Commission (CNSSTC). 2002. Noise and Vibration. Http://www.ci.las-vegas.nv.us/Files/NOISE AND VIBRATION.pdf. March. Carlson, T.J. 1994. Use of Sound for Fish Protection at Power Production Facilities: A Historical

Perspective of the State of the Art. Phase I Final Report: Evaluation of the Use of Sound to Modify the Behavior of Fish. Report No. DOE/BP-62611-4. Prepared for U.S. Department of

Energy; Bonneville Power Administration; Environment, Fish, and Wildlife. November.

- Chandonnet, A. 1979. The Once and Future Village of Ikluat/Eklutna: A History of a Tanaina Athapaskan Settlement. Adams Press, Chicago.
- Coffman Engineers, Inc. 2005. Personal communication from Dan Stears, Engineer. Regarding information on cathodic protection at the Port of Anchorage. 7 January.
- Colonel, J. M. and D. F. Jones. 1990. An Investigation of Sedimentation Processes in the Vicinity of the Ship Creek Waterfront Development, Draft Report.
- Cultural Resources Consultants (CRC) and HDR. 2003. Anchorage Intermodal Transportation Center Historic Resources Technical Report. Prepared for Alaska Railroad Corporation and Federal Transit Administration (Appendix in Ship Creek Intermodal Transportation Center Environmental Assessment). January.
- Davis, N.Y. 1994. Progress Report. Ethnographic Land Use Patterns of Knik Arm, Alaska: Especially as they Relate to Elmendorf Air Force Base. Prepared for the Dena'ina Elders, National Park Service, and Elmendorf Air Force Base.
- Department of the Navy. 2001. Final Overseas Environmental Impact Statement and Environmental Impact Statement for Surveillance Towed Array Sensor System Low Frequency Active (SURTASS LFA) Sonar. January.
- Facey, D.E., J.D. McCleave, and G.E. Doyon. 1977. Responses of Atlantic Salmon Parr to Output of Pulsed Ultrasonic Transmitters. *Transactions of the American Fisheries Society* 106:489-496.
- Fall, J.A., N.Y. Davis, and the Dena'ina Elders. 2003. An Overview of Dena'ina Athabaskan
 Uses on Sites on and near Elmendorf Air Force Base, Alaska. Prepared for U.S. Army Corps of
 Engineers. June.
- Federal Highway Administration (FHWA). 2000. Highway Traffic Noise in the United States, Problem and Response. U.S. Department of Transportation Federal Highway Administration. April.
- Federal Highway Administration (FHWA) and Alaska Department of Transportation and Public Facilities (ADOT&PF). 1984. Knik Arm Crossing Draft Environmental Impact Statement and Section 4(f) Evaluation.
- Federal Transit Administration (FTA). 2003. Essential Fish Habitat Assessment, Knik Arm Ferry Project. 6 March. Prepared for Federal Transit Administration and Matanuska-Susitna Borough (Appendix in Knik Arm Ferry Environmental Assessment). 6 March.

- Federal Transit Administration (FTA) and Alaska Railroad Corporation (ARRC). 2003. Ship Creek Intermodal Transportation Center Environmental Assessment. April.
- Federal Transit Administration (FTA) and Matanuska-Susitna Borough (MSB). 2003. Final Knik Arm Ferry NEPA Environmental Assessment. Prepared by HDR Alaska, Inc. June.
- Finneran, J. J., C.E. Schlundt, D.A. Carder, J.A. Clark, J.A. Young, J.B. Gaspin, and S.H. Ridgeway. 2000. Auditory and Behavioral Responses of Bottlenose Dolphins (*Tursiops truncatus*) and a Beluga Whale (*Delphinapterus leucas*) to Impulsive Sounds Resembling Distant Signatures of Underwater Explosions. *Journal of Acoustic Society of America* 108:417-431.
- Geotechnical Advisory Commission (GAC). 2004. A Resolution Regarding the Port of Anchorage Marine Terminal Project. Municipality of Anchorage. 5 April.
- Gill, R.E. and T.L. Tibbitts. 1999. Seasonal Shorebird Use of Intertidal Habitats in Cook Inlet, Alaska. OCS Study MMS 99-0012. September.
- Golder Associates, Inc. 2004. Port of Anchorage Road and Rail Expansion Geotechnical Investigation, Anchorage, Alaska. Prepared for Anchorage Port Expansion Team, Integrated Concepts and Research Corporation. July.
- Great Land Trust. 2000. Technical Report on Significant Natural Open Space in the Anchorage Bowl: A Survey of Biologically Important Habitat and Areas Identified as Important by the Anchorage Community. January.
- Groot, C. and L. Margolis. 1991. *Pacific Salmon Life Histories*. University of British Columbia Press, Vancouver, BC, Canada.
- Haas, M.E., C.A. Simenstad, J.R. Cordell, D.A. Beauchamp, and B.S. Miller. 2002. Effects of large overwater structures on epibenthic juvenile salmon prey assemblages in Puget Sound,
 Washington. Prepared for Washington State Transportation Commission in cooperation with the U.S. Department of Transportation, Federal Highway Administration. June.
- Harris Miller & Hanson (HMMH), Inc. 2003. Anchorage Rail Capacity Improvements Milepost 110-114 Noise and Vibration Study. Report No. 298680.01. January.
- Hastings, M.C., A.N. Popper, J.J. Finneran, and P.J. Lanford. 1996. Effects of Low Frequency Underwater Sound on Hair Cells of the Inner Ear and Lateral Line of the Teleost Fish, *Astronotus ocellatus*. *Journal of the Acoustical Society of America* 99:1759-1766.

- HDR Alaska, Inc. 2003. Ship Creek Intermodal Transportation Center, Transportation Impact Analysis Report. Prepared for Alaska Railroad Corporation. March.
- Hendrickson, G.B. 2004. Recommendations to Mitigate the Effects of Port Expansion on 381 IS

 Mission. Letter to the Manager of Government/Environmental Affairs for the Port of Anchorage.

 4 May.
- Kahler, T., M. Grassley, and D. Beauchamp. 2000. Summary of the Effects of Bulkheads, Piers, and Other Artificial Structures and Shorezone Development on ESA-listed Salmonids in Lakes. Prepared for City of Bellevue, WA. 13 July.
- Kari, J. and J.A. Fall. 1987. Shem Pete's Alaska: The Territory of the Upper Cook Inlet Dena'ina, 2nd Edition. Shem Pete, Principal Contributor. Alaska Native Language Center, University of Alaska, CIRI Foundation, Fairbanks, AK.
- Kari, P.R. 1987. Tanaina Plantlore Dena'ina K'et'una: An Ethnobotany of the Dena'ina Indians of Southcentral Alaska, Second Edition, Revised. National Park Service, Alaska Region.
- Knik Arm Bridge and Toll Authority (KABATA). 2004. Knik Arm Crossing Project Presentation. Http://steve2.xplorex.com. 7 June.
- Knudsen, F.R., P.S. Enger, and O. Sand. 1994. Avoidance Responses to Low Frequency Sound in Downstream Migrating Atlantic Salmon Smolt, *Salmo salar*. *Journal of Fish Biology* 45:227-233.
- _____. 1992. Awareness Reactions and Avoidance Responses to Sound in Juvenile Atlantic Salmon, Salmo salar. Journal of Fish Biology 40:523-534.
- Knudsen, F.R., C.B. Schreck, S.M. Knapp, P.S. Enger, and O. Sand. 1997. Infrasound produces flight and avoidance responses in Pacific juvenile salmonids. *Journal of Fish Biology* 51:824-829.
- LaBelle, J., J. L. Wise, R. Voelker, R. Schulze, and G. Whol. 1983. *Alaska Marine Ice Atlas*. University of Alaska, AEIDC.
- LGL Associates. 2004. A Proposal to Assess the Use of Knik Arm, Cook Inlet, Alaska by Beluga
 Whales in July October 2004, Record Sounds from Pile-driving Construction Activities at the
 Point MacKenzie Dock Modification, and Develop a Mitigation Strategy for Construction of the
 Knik Arm Bridge. Knik Arm Bridge and Toll Authority. June.

- McMahan, D.J. and C.E. Holmes. 1996. Archaeological Survey of Elmendorf Air Force Base, Alaska: Final Report. Alaska Office of History and Archaeology Report Number 61.
- Moore, S.E., K.E. Shelden, L.L. Litzky, B.A. Mahoney, and D.J. Rugh. 2000. Beluga, *Delphinapterus leucas*, Habitat Associations in Cook Inlet, Alaska. *Marine Fisheries Review* 62:60-80.
- Morgan, L. 1974. And the Land Provides; Alaskan Natives in a Year of Transition. Anchor Press, Garden City, NY.
- Moulton, L. L. 1997. Early Marine Residence, Growth, and Feeding by Juvenile Salmon in Northern Cook Inlet, Alaska. *Alaska Fishery Research Bulletin* 4:154–177.
- Mulherin, N.D., W.B. Tucker III, O.P. Smith, and W.J. Lee. 2001. Marine Ice Atlas for Cook Inlet, Alaska. May.
- Municipal Light and Power (ML&P). 2004. Conversations with ML&P Concerning Future Electrical Requirements Upon Completion of the POA Expansion Project. 10 June.

Municipality of Anchorage (MOA). 2004. Personal Communication from Tom Korosei, Parks and

Recreation Department. Regarding information on parks in the vicinity of the Port of Anchorage.

2003a. Comprehensive Economic Development Strategy. June.

2003b. 2004-2006 Transportation Improvement Program and 2001 Long-Range Transportation Plan Air Quality Conformity Determination. Public Review Draft. 10 March.

2002. 2002 Annual Report, NPDES Permit No. AK05255-8. Watershed Management Section. 2 January.

2001a. Anchorage 2020 Anchorage Bowl Comprehensive Plan. Planning Department. 21 February.

2001b. Year 2000 Anchorage Carbon Monoxide Attainment Plan. Air Quality Program Environmental Services Division, Department of Health and Human Services. 25 September.

2000. Ship Creek Multi-Modal Transportation Plan. December.

___. 1999a. Erosion and Sediment Control and Materials Containment Guidance Manual. Prepared

by CH2M Hill for the Watershed Management Section. January.

	004d. Personal communication from Brad Smith, Marine Mammalogist. Regarding information n beluga whale distribution and habitats in the vicinity of the Port of Anchorage. 8 October.
	004e. EFH for the North Pacific Council: EFH Mapping and Queryable Database. Http://akrnapping.fakr.noaa.gov/Website/EFH/viewer.htm (accessed 16 February 2004).
Е	2004f. Endangered Species Act Section 7 Formal Consultation and Magnuson-Stevens Act ssential Fish Habitat Consultation for the SR 104 Edmonds Ferry Terminal Project (HUC 7110019, Puget Sound). Northwest Region, Seattle, WA. 25 March.
	2003a. Draft 2003 Stock Assessment Reports. Office of Protected Resources. Alaska. http://www.nmfs.noaa.gov/prot_res/PR2/Stock_Assessment_Program/sars_draft.html.
	003b. Subsistence Harvest Management of Cook Inlet Beluga Whales Final Environmental mpact Statement. July.
	000. Designating the Cook Inlet, Alaska, Stock of Beluga Whale as Depleted Under the Marine Iammal Protection Act (MMPA). Federal Register 65:34590-34597.
	Oceanographic and Atmospheric Administration Ocean Service (NOAA Ocean Service). 2003. idal Bench Marks. Http://www.co-ops.nos.noaa.gov/benchmarks/9455920.html. 21 April.
	Register Information System (NRIS). 2004. Anchorage, AK. Http://www.nr.nps.gov/accessed 2 June 2004).
D	J., A. Turnpenny, J. Lanworth, and B. Edwards. 2003. Measurements of Underwater Noise uring Piling at the Red Funnel Terminal, Southampton, and Observations of its Effect on Caged ish. Http://www.subacoustech.com/downloads/558R0207.pdf. 27 October.
	Engineers, Inc. 1988. Draft Fire Island Crossing Issue Analysis. Department of Public Works funicipality of Anchorage. September.
	004a. Summary of July Sampling Activities – Knik Arm, Alaska. Prepared for HDR Alaska, c. 13 August.
	004b. Summary of August Sampling Activities – Knik Arm, Alaska. Prepared for HDR laska, Inc. 6 October.

- Reid Middleton, Inc. 1993. Port Area Transportation Analysis for Port of Anchorage. File: 40-92-008-001-01. February.
- Richardson, W.J., C.R. Greene, C.I. Malme, and D.H. Thomson. 1995. *Marine Mammals and Noise*. Academic Press, Inc., San Diego, CA.
- Ridgway, S.H., D.A. Carder, R.R. Smith, T. Kamolnick, C.E. Schlundt, and W.R. Elseberry. 1997. Behavioral Responses and Temporary Shift in Masked Hearing Threshold of Bottlenose Dolphins, *Tursiops truncatus*, to 1-second Tones of 141 to 201 dB re 1 μPa. Technical Report 1751. Naval Command, Control and Ocean Surveillance Center, RDT&E Division. July.
- Rugh, D.J., B.A. Mahoney, C.L. Sims, B.K. Smith, and R.C. Hobbs. 2004a. Aerial Surveys of Belugas in Cook Inlet, Alaska, June 2003. http://www.fakr.noaa.gov/protectedresources/whales/beluga/surveyrpt2003.pdf. 9 February.
- Rugh, D.J., B.A. Mahoney, and B.K. Smith. 2004b. Aerial Surveys of Beluga Whales in Cook Inlet, Alaska, between June 2001 and June 2002. NOAA Technical Memorandum NMFS-AFSC-145. July.
- Rugh, D.J., K.E.W. Sheldon, CL. Sims, B.A. Mahoney, B.K. Smith, and R.C. Hobbs. 2004c. Aerial Surveys of Belugas in Cook Inlet, Alaska, June 2004.
 Http://www.fakr.noaa.gov/protectedresources/whales/beluga/survey/2004.pdf. 9 December.
- Shannon and Wilson, Inc. 1999. Draft Final Risk Assessment, Defense Fuel Support Point Anchorage, Alaska. January.
- Sheldon, K.E.W., R.A. Mahoney, and M.E. Dahlheim. 2003. Killer Whale Predation on Belugas in Cook Inlet, Alaska: Implications for a Depleted Population. *Marine Mammal Science* 19:529-544.
- Simenstad, C.A., B.J. Nightingale, R.M. Thom, and D.K. Shreffler. 1999. Impacts of Ferry Terminals on Juvenile Salmon Migrating along Puget Sound Shorelines; Phase I: Synthesis of State of Knowledge. Prepared for Washington State Transportation Commission in cooperation with the U.S. Department of Transportation, Federal Highway Administration. June.
- Smith, B. 2003. Conversation between Brad Smith, National Oceanic and Atmoshpheric Administration Fisheries Field Office Supervisor, and Heather Hammond, HDR Alaska, Inc. environmental planner. Regarding beluga whales and other marine mammals in the Port of Anchorage vicinity.

Smith, O. 2000. Formation and Decay of Stamukhas, Cook Inlet, Alaska, in Proceedings, 15th International Symposium on Ice. Gdansk, Poland, 28 August – 1 September. Terracon, Inc. 2003. Intermodal Expansion Port of Anchorage, Volume I. Prepared for Koniag Services. Inc. 11 December. Tryck, Nyman, Hayes. 2002. Design Study Report. Proposal Submitted to the Port of Anchorage Intermodal Marine Facility. March. United States Air Force (Air Force). 2004. Environmental Restoration Program. LF04 2003 Debris Removal Report. Elmendorf Air Force Base. March. 2003. Environmental Restoration Program. Source LF04 Operations and Management Plan. Elmendorf Air Force Base. November. 2001. Initial F-22 Operational Wing Beddown. Draft Environmental Impact Statement. Elmendorf Air Force Base. April. . 1997. Operable Unit 6 and Source Area SS19 Record of Decision. Elmendorf Air Force Base. January. 1996. Environmental Restoration Program. Remedial Investigation/Feasibility Study Report. Operable Unit 6. Volume I. Elmendorf Air Force Base. January. United States Air Force Center for Environmental Excellence (AFCEE). 2002. Site Investigation at Area of Concern 97, Cherry Hill Ravine, Final Report. AFCEE Contract No. F41624-95-D-8004, Delivery Order 0055. January. United States Army (Army). 2004. Personal Communication from Phillip Fantosi, Chief of Terminal Operations, 333rd Transportation Battalion. Regarding Deployment of the Stryker Brigade. United States Army/Alaska (USARAK). 2004a. Personal Communication from William Peak, Fort Richardson Facility Manager. Regarding Information on Whittier to Anchorage Military Pipeline. 2004b. Transformation of U.S. Army Alaska. Final Environmental Impact Statement. May. United States Army Corps of Engineers (USACE). 2003. Anchorage Harbor, Alaska, Condition of

Improvement. 30 September.

_. 1992. Storm Water Management for Construction Activities: Developing Pollution and

Prevention Plans and Best Management Practices (EPA Document 832 R-92-005). September.

on 4 May 2004.

United States Fish and Wildlife Service (USFWS). 2004a. Endangered and Threatened Wildlife and Plants; Listing the Southwest Alaska Distinct Population Segment of the Northern Sea Otter (Enhydra lutris kenyoni) as Threatened. Federal Register 69:6600-6621.
2004b. Personal Communication from Bill Knauer, Office of Subsistence Management. Regarding subsistence use of Anchorage Harbor.
1995. Draft Coordination Act Report for Cook Inlet Navigation Study. Ecological Services. August.
1993. Comments on the Draft Ship Creek – Port Area Meriting Special Attention (AMSA) Plan. Personal communication via letter from Rosa Meehan, Acting Field Supervisor, to Michael Meehan, Director, Department of Economic Development and Planning, Municipality of Anchorage. 4 January.
United States Geological Survey (USGS). 1999. Precipitation-Runoff, Suspended-Sediment, and Flood-Frequency Characteristics for Urbanized Areas of Elmendorf Air Force Base, Alaska. Water-Resources Investigations Report 98-4265. Prepared in conjunction with the U.S. Air Force.
Updike, R.G. 1986. Engineering Geological Maps of the Government Hill Area, Anchorage, Alaska. Prepared for U.S. Geological Survey.
Vickerman, Zachary, Miller and TranSystems Corporation (VZM). 1999. Regional Port of Anchorage Master Plan. Final Report. Prepared for the Port of Anchorage. 3 September.
1996. Port of Anchorage Traffic Flow Study. Prepared for the Port of Anchorage. 7 February.
Werner, Stuart D. 1998. Seismic Guidelines for Ports. Technical Council on Lifeline Earthquake Engineering, monograph No. 12, American Society of Civil Engineers. March.

CHAPTER 6

PERSONS AND AGENCIES CONTACTED

6.0 PERSONS AND AGENCIES CONTACTED

Anderson, Cindy. Alaska Department of Natural Resources.

Anderson, Duane. R&M Consultants.

Berg, Catherine. Project Planning, U.S. Fish and Wildlife Service.

Bittner, Judith. State Historic Preservation Officer, Office of History and Archaeology, Division of Parks and Recreation, Alaska Department of Natural Resources.

Boland, Lt. Mark. Habitat Conservation, Fisheries, National Oceanic and Atmospheric Administration.

Brewer, Andrew. Operations Branch, U.S. Army Corps of Engineers, Alaska District.

Bruce, Kevin. Director of Communications and Business Development, Port of Anchorage.

Buirge, Dave. U.S. Army Alaska, Fort Richardson.

Burnell, Connie. Native Village of Tyonek.

Churchill, Allen. Chief, Operations and Readiness Branch, U.S. Army Corps of Engineers, Alaska District.

Coppe, Cheryl. Executive Administrator, Port Development, Port of Anchorage.

Dale, Joan. Archaeologist, Office of History and Archaeology, Division of Parks and Recreation, Alaska Department of Natural Resources.

Davis, Nancy Yaw. Anthropologist, Cultural Dynamics.

Dean, Heather. Environmental Scientist, Environmental Protection Agency, Region 10.

Ebersole, Bruce. Chief, Coastal Processes Branch, U.S. Army Engineer Research and Development Center.

Eises, Ken. U.S. Army Corps of Engineers, Alaska District.

Encelewski, Richard. Ninilchik Village Traditional Council.

Fantosi, Phillip. Chief, Terminal Operations, 333rd Transportation Battalion, U.S. Army.

Gardner, Kevin. Environmental Planner, U.S. Army Alaska, Fort Richardson.

Godden, Ellen. Restoration, 3rd Civil Engineering Squadron/Environmental Restoration, Elmendorf Air Force Base.

Graves, Roger. Manager, Government/Environmental Affairs, Port of Anchorage.

Greydanus, Stuart. Operations Manager, Port of Anchorage.

Griese, Herman. 3rd Civil Engineering Squadron/Environmental Restoration, Elmendorf Air Force Base.

Hanson, Jeanne. Fisheries, National Oceanic and Atmospheric Administration.

Harrison, Thomas. Executive Officer, Marine Safety Office, U.S. Coast Guard.

Hendrickson, Col. Gordon. 381st Intelligence Squadron, Elmendorf Air Force Base.

Henry, Amanda. Office of Project Management and Permitting, Alaska Coastal Management Program, Alaska Department of Natural Resources.

Holtery, LTC Michelle. Alaska Command, Elmendorf Air Force Base.

Hughes, Steven. Senior Research Coastal Engineer, U.S. Army Engineer Research and Development Center.

Kahn, Lynnda. Fish and Wildlife Biologist, U.S. Fish and Wildlife Service.

Kashevaroff, Don. Seldovia Village Tribe.

Keller, Bill. Regulatory Branch, U.S. Army Corps of Engineers, Alaska District.

Knauer, Bill. Office of Subsistence Management, U.S. Fish and Wildlife Service.

Korosei, Tom. Parks and Recreation Department, Municipality of Anchorage.

Kuk, Kim. Operations Branch, U.S. Army Corps of Engineers, Alaska District.

Lance, Brian. Fisheries, National Oceanic and Atmospheric Administration.

Lawton, Ann. Chief, Conservation, 3rd Civil Engineering Squadron/Environmental Planning, Elmendorf Air Force Base.

Lemons, Mark. 381st Intelligence Squadron, Elmendorf Air Force Base.

Lenz, Julia. Research Technician, Alaska Natural Heritage Program.

Leon, Ed. Financial Officer, Port of Anchorage.

Ludwig, Stephanie. Archaeologist. Office of History and Archaeology, Division of Parks and Recreation, Alaska Department of Natural Resources.

Magee, Sue. Office of Project Management and Permitting, Alaska Coastal Management Program, Alaska Department of Natural Resources.

Mahoney, Barbara. Marine Mammal Specialist, Fisheries, National Oceanic and Atmospheric Administration.

Mann, Frances. Project Planning, U.S. Fish and Wildlife Service.

McMahan, Dave. State Archaeologist, Office of History and Archaeology, Division of Parks and Recreation, Alaska Department of Natural Resources.

Morris, Capt. Ron. U.S. Coast Guard Marine Safety Office, Anchorage.

Ondola, George. Dena'ina Elder.

Ondola, Suzie. Dena'ina Elder.

Oliver, John. Consultant, U.S. Army Corps of Engineers, Alaska District.

Peak, William. Facilities Manager, U.S. Army Alaska, Fort Richardson.

Peltz, Larry. Fisheries, National Oceanic and Atmospheric Administration.

Raymond-Yakoubian, Julie. Archaeologist, Office of History and Archaeology, Division of Parks and Recreation, Alaska Department of Natural Resources.

Reakert, Jim. Coastal Management Program, Alaska Department of Natural Resources.

Richmond, Allen. Chief, Conservation, 3rd Civil Engineering Squadron/Environmental Planning, Elmendorf Air Force Base.

Rumfelt, Tim. Environmental Scientist, Alaska Department of Environmental Conservation.

Seaberg, Stewart. Office of Project Management and Permitting, Alaska Department of Natural Resources.

Senner, Stan. Director, Anchorage Audubon Society.

Sheffield, Governor William. Port Director, Port of Anchorage.

Sims, Christy. Marine Mammal Data Specialist, National Marine Mammal Laboratory.

Smagge, Rita. Kenaitze Indian Tribe.

Smith, Brad. Field Office Supervisor, Fisheries, National Oceanic and Atmospheric Administration.

Springer, Henry. Program Manager, Knik Arm Bridge and Transit Authority.

Stears, Dan. Engineer, Coffman Engineers, Inc.

Stephan, Alberta. Dena'ina Elder.

Stephan, Lee. Chief Executive Officer, Native Village of Eklutna.

Stephan, Leo. Dena'ina Elder.

Theodore, Carol. Knik Tribal Council.

Thomasson, M. Planner, 3rd Civil Engineering Squadron/Environmental Planning, Elmendorf Air Force Base.

Tobish, Thede. Planning Department, Municipality of Anchorage.

Tover, Art. 381st Intelligence Squadron, Elmendorf Air Force Base.

Voss, Dan. Biologist, Fisheries, National Oceanic and Atmospheric Administration.

Wade, Douglas. Native Village of Chickaloon.

Whitney, John. Scientific Support Coordinator, National Oceanic and Atmospheric Administration.

Winn, Ryan. Project Manager, Regulatory Branch, U.S. Army Corps of Engineers, Alaska District.

Yuska, Daniel. Environmental Protection Specialist, U.S. Department of Transportation Maritime Administration.

CHAPTER 7

LIST OF PREPARERS AND CONTRIBUTORS

7.0 LIST OF PREPARERS AND CONTRIBUTORS

Peer Amble, Alternatives Analysis Process, The Environmental Company, Inc.

B.A., Geography, University of California, Santa Barbara, 1988

Years of Experience: 14

Marianne Aydil, Air Quality, The Environmental Company, Inc.

B.S., Chemical Engineering, Tulane University, 1987

Ph.D., Chemical Engineering, University of Houston, 1992

Years of Experience: 11

Craig Bloxham, Quality Assurance Review, The Environmental Company, Inc.

B.A., Geography, University of California, Santa Barbara, 1985

M.A., Geography, University of California, Santa Barbara, 1989

Years of Experience: 16

Diana Brake, Project Description, Integrated Concepts and Research Corporation

B.S., Civil Engineering, University of Idaho, 1995

Years of Experience: 8

Soo Choi, Data Collection, Integrated Concepts and Research Corporation

B.S., Electrical Engineering, Illinois Institute of Technology, 2004

Years of Experience: 2

Michael Costonzo, Socioeconomics, The Environmental Company, Inc.

B.A., Geography, University of California, Santa Barbara, 1979

M.A., Geography, University of California, Santa Barbara, 1981

Ph.D., Geography, University of California, Santa Barbara, 1985

Years of Experience: 24

Christina Cummings, Production Coordinator/Environmental Analyst, The Environmental Company, Inc.

A.A.S., Administrative Office Technology, Boise State University, 1999

Years of Experience: 5

Christine Davis, Hazardous Materials and Waste/Geology and Soils, The Environmental Company, Inc.

B.S., Environmental Studies, University of California, Santa Barbara, 1998

M.S., Environmental Management, University of San Francisco, 2000

Years of Experience: 5

Stephen Dewan, Cultural Resources, Clarus Technologies LLC

B.S., Sociology, North Dakota State University, 1976

M.A., Business Organizational Management, University of LaVerne, 1996

Years of Experience: 14

Greg Douglas, Alternatives Analysis Process, TEC Infrastructure Consultants

Undergraduate, Architecture, Northern Alberta Institute of Technology, Canada, 1992

Years of Experience: 12

James Fee, Geographic Information Systems, The Environmental Company, Inc.

B.S., Geography, Arizona State University, 1996

Years of Experience: 8

Chareé D. Hoffman, Land Use and Coastal Zone Consistency, The Environmental Company, Inc.

B.S., Biology, Christopher Newport University, 1999

Years of Experience: 5

William E. Humphries, Project Description, Integrated Concepts and Research Corporation

B.A., Environmental Management, University of North Carolina, 1977

M.S., Watershed Science, Utah State University, 1981

Years of Experience: 23

Michael Lucas, Noise, The Environmental Company, Inc.

B.S., Physics, Moravian College, 1981

M.S., Mechanical Engineering, Lehigh University, 1983

M.S., Fluid Mechanics, von Karman Institute, 1985

Years of Experience: 15

Edie Mertz, Graphics, The Environmental Company, Inc.

A.A., General Education, Cerro Coso College, 1994

Years of Experience: 13

Wesley Miksa, Transportation and Traffic/Public Services and Utilities, The Environmental Company,

B.A., Philosophy/Environmental Studies, Lawrence University, 2002

M.P.A., Earth Systems Science Policy and Management, Columbia University, 2003

Years of Experience: 3

Bonnie Morris, Cultural Resources, Clarus Technologies LLC

B.A., Anthropology/Archaeology, State University of New York, Buffalo, 1991

Year of Experience: 12

Dan Muslin, Hydrodynamics and Sedimentation, TEC Infrastructure Consultants

B.S., Engineering, California State Polytechnic University, Pomona, 1971

Years of Experience: 33

Dana Novak, Recreation and Visual, The Environmental Company, Inc.

B.S., Environmental Science, Ohio State University, 1997

Years of Experience: 6

Bill Palmer, Geographic Information Systems, The Environmental Company, Inc.

B.A., Economics, University of Virginia, 1998

M.A., Planning, University of Virginia, 2000

Years of Experience: 4

Kevin J. Peter, Program Manager and Quality Control, The Environmental Company, Inc.

B.A., Anthropology, Pomona College, 1975

M.A., Anthropology, Washington State University, 1986

Years of Experience: 24

Ryan Pingree, Water Quality, The Environmental Company, Inc.

B.S., Physical Geography, University of California, Santa Barbara, 1996

M.S., Environmental Science and Management, University of California, Santa Barbara, 1999

Years of Experience: 8

James Reed, Project Description, TEC Infrastructure Consultants

B.S., Civil Engineering, Montana State University, 1981

M.S., Civil Engineering, Johns Hopkins University, 1993

Years of Experience: 22

Kathy Rose, Technical Editor/Public Involvement, The Environmental Company, Inc.

B.A., Political Science/German, University of Massachusetts, 1980

M.A., International Relations, George Washington University, 1983

M.S., Forest Resource Management, University of Idaho, 1996

Years of Experience: 8

Teresa Rudolph, Project Manager, The Environmental Company, Inc.

B.A., Anthropology, Florida State University, 1975

M.A., Anthropology, Southern Illinois University, 1981

Years of Experience: 23

Rick Spaulding, Biology, The Environmental Company, Inc.

B.A., Biology, University of California, 1982

M.S., Wildlife and Fisheries Science, University of Arizona, 1996

Years of Experience: 17

Patricia Spengler, Word Processing, The Environmental Company, Inc.

Years of Experience: 22

Isla Stevenson, Environmental Justice, The Environmental Company, Inc.

B.A., Anthropology, Boise State University, 2001

Years of Experience: 3

Marcel Veilleux, Alternatives Analysis Process, TEC Infrastructure Consultants

B.S., Civil Engineering, University of Massachusetts, 1981

Years of Experience: 22

Jennifer Weitkamp, Biology, The Environmental Company, Inc.

B.S., Fisheries Biology, University of Washington, 1995

Years of Experience: 9

APPENDIX A

PUBLIC INVOLVEMENT

APPENDIX A PUBLIC INVOLVEMENT

INTRODUCTION

Public involvement is at the heart of NEPA. It ensures that potentially affected communities (whether they are Government Hill residents; federal, state, and/or local government agencies; Native Alaskan villages and tribes; interest groups; or private citizens) are informed and involved in the NEPA and decision-making process.

For purposes of the Project, public involvement includes:

- Notifying government agencies and organizations early in the development of the Project to identify potential effects on the natural and/or human environment.
- Holding public meetings (when appropriate) during the early stage of the NEPA process to
 provide information to the public, receive comments, and identify any issues or concerns the
 public might have with the Project efforts.
- Advertising meetings in local newspapers (including Anchorage and surrounding communities) to ensure broadest dissemination of the NEPA-related efforts.
- Preparing informative posters/displays and newsletters covering the Project and alternatives, possible environmental issues, and the environmental and consultation process.

Scoping is an important aspect of public involvement that ensures public input early in the environmental analysis process, identifies community-specific issues and concerns, and solicits potential viable alternatives to expansion efforts. This appendix presents an analysis of written and verbal responses of issues and concerns raised during the scoping period for the Marine Terminal Redevelopment EA.

Scoping identifies the issues and concerns that are of particular interest to the affected populace. This information is then used to assist resource specialists in data collection and analysis for the draft EA development process. This summary is based on all public written comments received from January 15, 2004 to February 15, 2004 (the official scoping period) and agency comments received from January through June 2004.

SCOPING PROCESS

The first step in scoping was the public announcement of the POA's intention to conduct an EA for the Project. Advertisements were placed a week before the meeting in the *Anchorage Daily News* and the *Frontiersman*, describing the proposal and alternatives. The advertisement invited the public to attend the scoping open house on January 15, 2004 and provided the time, date, and the location of the meeting. In

addition to the advertisements, a flyer inviting Anchorage citizens to the scoping meeting was also sent to 850 recipients, including Government Hill residents, interest groups, and local companies.

In addition to public scoping, the POA conducted three agency scoping meetings – on January 12, 2004, February 26, 2004, and June 24, 2004 – to solicit concerns from local, state, and federal agency representatives. The POA also conducted separate meetings with the USACE, NOAA Fisheries, Alaska SHPO, and Native Alaskan elders.

PUBLIC SCOPING MEETING

The scoping meeting was designed in an "open house" format to create a comfortable atmosphere for attendees. POA, MARAD, and Anchorage Port Expansion Team representatives were available to answer any questions and address issues and concerns from citizens.

The open house meeting was held at Egan Convention Center in Anchorage. Attendees were welcomed at the door by Anchorage Port Expansion Team members. The greeters asked attendees to sign-in, distributed hand-out materials, and directed them to the first display.

Six displays were developed to inform the public. These were designed to enhance public understanding of the NEPA process, the need for the proposed action, how the alternatives were designed and selected, the composition of the Anchorage Port Expansion Team, and the current status of the Project. A bathymetric map of Cook Inlet and an electronic and poster presentation of the USACE flow table for the POA were also shown to the public. All scoping materials, as well as the displays used at the meeting, are posted on the Anchorage Port Expansion website at www.portofanchorage.org.

The public was provided several venues for commenting during the scoping period. Attendees could submit written comments they brought with them, complete a comment form provided by the Anchorage Port Expansion Team, send comments to the Anchorage Port Expansion Team address, or e-mail comments to expansioncomment@portofanchorage.org.

SCOPING MEETING SCHEDULE

The Anchorage Port Expansion Team planned a scoping meeting at one location in Anchorage; the schedule, location, and attendance level for the scoping meeting is provided in Table A-1.

Table A-1 Schedule of Meeting and Attendance				
City/Town	Date	Location	Number of Attendees	
Anchorage	January 15, 2004	William A Egan Civic & Convention Center, Summit Room	41	

COMMENT AND ISSUE SUMMARY

Table A-2 outlines the number of attendees and comments received (either written or computer-generated) during the scoping period.

Table A-2 Scoping Meeting Comment Summary				
Scoping Location Attended Comments				
Anchorage	41	3		

The three public comments ranged from support for the POA expansion, to a question regarding choice of alternatives and why the POA cannot be moved to Fire Island, to an email requesting examination of scouring, sedimentation, and dredging.

AGENCY SCOPING MEETINGS

Issues of concern mentioned at the three agency scoping meetings include effects on:

- Traffic and transportation;
- Air quality;
- Noise impacts from construction and operations on neighborhoods;
- Beluga whales;
- Fish habitat;
- Shorebirds;
- Safety;
- Water quality;
- Cultural resources;
- Hazardous materials and waste;
- Local plans;
- Local and state economy; and
- Cumulative actions in the area.

A summary of these comments are included in the Agency Comment Matrix in Table A-3.

	Table	A-3 Agency Comment Matrix	
Sources of Comments or Issues	Agency or Entity	Issue	Addressed in EA
1-12-04 Agency Scoping Mtg.	MOA, Planning Department	How well will traffic flow at full build out? How will traffic affect air quality?	Section 3.4.3 Transportation
1-12-04 Agency Scoping Mtg.	MOA, Planning Department	Where will gravel come from?	Section 3.3.1 Geology and Soils
1-12-04 Agency Scoping Mtg.	MOA, Planning Department	How does the EA fit into the Master Plan? Will the Master Plan be updated?	Section 3.4.1 Land Use and Coastal Zone Consistency
1-12-04 Agency Scoping Mtg.	MOA, Planning Department	How will spill plans and emergency response issues be dealt with?	Section 3.3.3 Water Quality
1-12-04 Agency Scoping Mtg.	MOA, Planning Department	How will full build out affect city planning?	Section 3.4.1 Land Use and Coastal Zone Consistency
1-12-04 Agency Scoping Mtg.	MOA, Planning Department	Will increased operations affect fish & wildlife?	Section 3.3.4 Biological Resources
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	Will POA expansion interfere with access to LF04 and how will it affect the ROD?	Section 3.2.3 Hazardous Materials and Waste
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	Security outside dock	Section 3.2.4 Safety
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	Visual impacts to Government Hill Historic District	Section 3.4.7 Cultural Resources
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	Location of fill for construction	Section 3.3.1 Geology and Soils
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	What are the cumulative effects of the bridge project with the POA expansion?	Chapter 4
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	What is the cumulative effect on belugas?	Chapter 4
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	How will the POA expansion relate to military staging decisions (Stryker Brigade)?	Chapter 1
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	What will be the effect of expansion on Elmendorf's flight line/ clear zone/lighting?	Section 3.2.4 Safety
l-12-04 Agency Scoping Mtg.	USEPA	Would wetlands be affected?	Section 3.3.4 Biological Resources
1-12-04 Agency Scoping Mtg.	USEPA	Air quality	Section 3.2.1 Air Quality

	Table A-3	Agency Comment Matrix (con't)	
Sources of Comments or Issues	Agency or Entity	Issue	Addressed in EA
1-12-04 Agency Scoping Mtg.	USEPA	What effect would the expansion have on water quality/stormwater runoff treatment?	Section 3.3.3 Water Quality
1-12-04 Agency Scoping Mtg.	Fort Richardson, Director of Public Works	How would it relate to military deployments?	Chapter 1
1-12-04 Agency Scoping Mtg.	U.S. Coast Guard, Marine Safety Office	How will it affect security plans for new facilities?	Chapter 1
1-12-04 Agency Scoping Mtg.	NOAA Fisheries	What will be the effect on beluga whales?	Section 3.3.4 Biological Resources
1-12-04 Agency Scoping Mtg.	NOAA Fisheries	What would be the effect of construction noise on belugas?	Section 3.3.4 Biological Resources
1-12-04 Agency Scoping Mtg.	NOAA Fisheries	Interested in increased public whale viewing areas north of boat launch	Section 3.3.4 Biological Resources
1-12-04 Agency Scoping Mtg.	NOAA Fisheries	How will stormwater runoff affect fish habitat?	Section 3.3.4 Biological Resources
1-12-04 Agency Scoping Mtg.	NOAA Fisheries	How will snow removal affect water quality?	Section 3.3.3 Water Quality
1-12-04 Agency Scoping Mtg.	NOAA Fisheries	Cumulative effects and impacts to the entrance to Ship Creek	Section 3.3.2 Hydrodynamics Section 4.4 Cumulative
1-12-04 Agency Scoping Mtg.	Elmendorf AFB, Alaska Command	Cumulative impacts (POA expansion and Knik Arm Bridge)	Section 3.3.2 Hydrodynamics Section 4.4 Cumulative
1-12-04 Agency Scoping Mtg.	Alaska SHPO	Ground disturbance in barge area and effects to archaeological sites	Section 3.4.7 Cultural Resources
1-12-04 Agency Scoping Mtg.	Alaska SHPO	Will material sources be surveyed?	Section 3.4.7 Cultural Resources
1-12-04 Agency Scoping Mtg.	Alaska SHPO	Two known archaeological sites within Project area limits	Section 3.4.7 Cultural Resources
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	Impact of noise on Cherry Hill housing area	Section 3.2.2 Noise
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	Effect of construction truck traffic on transportation	Section 3.4.3 Transportation

Table A-3 Agency Comment Matrix (con't)			
Sources of Comments or Issues	Agency or Entity	Issue	Addressed in EA
1-12-04 Agency Scoping Mtg.	Elmendorf AFB	Possible conflict with electronics and the Elephant Cage	Section 3.2.4 Safety
1-12-04 Agency Scoping Mtg.	ОРМР	Concerned about when to participate in review process	Section 2.4.2 Other Regulatory and Permit Requirements
1-12-04 Agency Scoping Mtg.	Fort Richardson	Ship Creek	Section 3.3.2 Hydrodynamics
1-12-04 Agency Scoping Mtg.	Fort Richardson	Operational issues/general concerns include construction impacts to Defense Fuels property	Section 3.2.3 Hazardous Materials and Waste
2-26-04 Agency Scoping Mtg.	U.S. Coast Guard	Effects on bird nesting	Section 3.3.4 Biological Resources
2-26-04 Agency Scoping Mtg.	USEPA	Biotic sampling	Section 3.3.4 Biological Resources
2-26-04 Agency Scoping Mtg.	NOAA Fisheries	Beluga whales migration and staging areas	Section 3.3.4 Biological Resources
2-26-04 Agency Scoping Mtg.	NOAA Fisheries	Dredging and Essential Fish Habitat	Section 3.3.5 Essential Fish Habitat
2-26-04 Agency Scoping Mtg.	NOAA Fisheries	Effects of sheet pile vs. pile-supported dock on fish	Section 3.3.4 Biological Resources
2-26-04 Agency Scoping Mtg.	ADNR	Migratory corridor for shore birds	Section 3.3.4 Biological Resources
2-26-04 Agency Scoping Mtg.	USFWS	Migratory birds	Section 3.3.4 Biological Resources
2-26-04 Agency Scoping Mtg.	Fort Richardson	Cumulative Impacts	Chapter 4
2-26-04 Agency Scoping Mtg.	NOAA Fisheries	Transportation effects	Section 3.4.3 Transportation
Correspondence	Individual	Tak'at Fish Camp	Section 3.4.7 Cultural Resources
3-1-04 381 Intelligence Squadron Mtg.	381 Intelligence Squadron Logistics/Maintenance	EM interference during construction, especially with welding and communications work	Section 3.2.4 Safety
3-1-04 381 Intelligence Squadron Mtg.	381 Intelligence Squadron Flight Commander	Suggested mitigating factors: shield power cables, low sodium lights	Section 3.2.4 Safety

	Table A-3 Agency Comment Matrix (con't)									
Sources of Comments or Issues	Agency or Entity	Issue	Addressed in EA							
3-1-04 381 Intelligence Squadron Mtg.	Airspace Manager, Elmendorf AFB	Relating to air traffic control tower on Elmendorf AFB (has 9 antennas)	Section 3.2.4 Safety							
1-28-04 USACE, Alaska District Mtg.	Operations Branch, USACE, Alaska District	What can 2D hydrographic model tell you?	Section 3.3.2 Hydrodynamics							
1-28-04 USACE, Alaska District Mtg.	Project Manager, Regulatory Branch, USACE, Alaska District	How much change in channel? Is it part of the environmental process?	Section 3.3.2 Hydrodynamics							
1-28-04 USACE, Alaska District Mtg.	Project Manager, Regulatory Branch, USACE, Alaska District	Where will the sediment go?	Section 3.3.1 Geology and Soils							
1-28-04 USACE, Alaska District Mtg.	Project Manager, Regulatory Branch, USACE, Alaska District	Why is the expansion so big?	Chapter 1							
2-5-04 USACE, Alaska District Follow-up Mtg.	Project Manager, Regulatory Branch, USACE, Alaska District	Reasons for not using landside instead of tidelands - AF property/Elephant Cage/CZ & APZ	Chapter 2							
2-5-04 USACE, Alaska District Follow-up Mtg.	Regulatory Branch, USACE, Alaska District	What impact will the POA expansion have on maintenance dredging?	Section 3.3.1 Geology and Soils							
2-26-04 USACE, Alaska District 2nd Follow-up Mtg.	Regulatory Branch, USACE, Alaska District	Loss of wetlands (tidelands)	Section 3.3.4 Biological Resources							
1-9-04 GAC Mtg.	Municipality of Anchorage	Socioeconomic benefits	Section 3.4.6 Socioeconomics							
1-9-04 GAC Mtg.	Geotechnical Advisory Committee	Seismic resistance	Section 3.3.1 Geology and Soils							


CONCLUSION


The scoping process for the Marine Terminal Redevelopment EA resulted in both public and agency input into the document. The public and agencies were adequately notified of the proposal and scoping process – 850 flyers were posted to local residents, three agency scoping meetings were conducted, and over 30 agency participants from federal, state, and local agencies gave input on issues and concerns. Forty-one people attended the public scoping meeting on January 15, 2004. The public was given ample opportunity to comment over the 30-day comment period; three comments were received. Relevant issues and concerns received during the scoping period were addressed in the draft EA.


In addition to public scoping, MARAD and the POA published the Draft Marine Terminal Redevelopment EA on August 11, 2004. The document publication was announced in the *Federal Register* (MARAD 2004a) and in local newspapers, and the document was made available to the public and agencies through public websites (www.portofanchorage.org and http://dms.dot.gov), at the Loussac Library, and by providing individual copies on request. A public comment period was held from August 11 to September 17, 2004 (MARAD 2004b). The goal during this process was to solicit comments concerning the analysis presented in the draft EA. MARAD and the POA received comments from the public, federal, state, and municipal agencies. Following the public comment period, a final EA was prepared. This document is a revision of the draft EA, including consideration of all comments, and provides the MARAD decisionmaker with a comprehensive review of the proposed action and alternatives and their potential environmental consequences. A summary of the comments received during the public comment period is included in Appendix H.

APPENDIX B


AREA CONSTRUCTION SEQUENCING










Appendix B: Area Construction Plans Final, March 2005









APPENDIX C

AIR QUALITY

Table C-1 Summary CO Emissions

Baseline CO Emissions (tons)							
Port Generated Traffic							
Truck	63						
Rail	0						
Auto	69						
Port Operations							
Crane	5						
Vessel	6						
Hostler 13							
TOTAL BASELINE	156						

Projected CO Emissions (tons)								
Port Generated Traffic	2010	2015	2020					
Truck	3	10	26					
Rail	1	1	1					
Auto	15	24	44					
Port Operations	:							
Crane	1	1	3					
Vessel	1	2	2					
Hostler	2	4	7					
Construction								
Maximum Season	73							
TOTAL CHANGE	96	41	83					

Table C-2 Summary Locomotive Operational CO Emissions

SD70 Locomotive Duty-cycle Average Fuel consumption

Line-haul gal/hour gal/hour 56 Switch 133 19

Change	Change from Baseline (annual)				1.09	2.17
Total Combined Annual CO	Emissions (tons)	00.0	0.00	1.09	1.09	2.17
Total CO Emission (tons)	Line Haul	00.0	00.00	0.45	0.45	06.0
Total CC (tv	Switch	00.0	0.00	0.64	0.64	1.28
CO Emission Factor (grams/gal)	Line Haul	26.6	26.6	26.6	26.6	26.6
CO Er	Switch	38.1	38.1	38.1	38.1	38.1
Daily Fuel Consumption (gal)	Line Haul	000.0	000.0	41.952	41.952	83.904
Dail Consi (e	Switch	0.000	0.000	41.640	41.640	83.280
ne in Mode rs/day)	Line Haul			0.25		0.25
Train Tim (hour	Switch	0.733	0.733	0.733	0.733	0.733
Train Movements	per day	0	0	_	_	2
Year		2003	2005	2008	2020	2025

Assumptions:

Trains each have 3 locomotives

Travel through Maintenance Area is 14 miles of ARRC track

4 miles is within the yards with a speed limit of 10 mph, and is characterized by switch operation

10 miles is outside of the yards with an average speed of 40 mph

Each train idles for 20 minutes within the yard area per train movement

gal = gallon

Table C-3 Vessel Calls Operational CO Emissions

Assumptions and Methodology based on the MOA Emission Calculation Procedures based on Emission Factors Derived from Procedures for Emission Inventory Preparation, Volume IV: Mobile Source EPA-450, 4-81-026d (revised), July 1989

Year	Total Vessel Calls	Vessel Calls	CO Emission Factors (per ship per day)			Total CO E	Change from Baseline	
	(per year)	(per day)	Dockside	Underway	Total	Daily	Annual	(annual)
2003	491	1	16	8	24	0	6	0
2005	514	1	16	8	24	0	6	0
2008	542	1	16	8	24	0	6	1 1
2010	565	2	16	8	24	0	7	1 1
2015	625	2	16	8	24	0	7	2
2020	690	2	16	8	24	0	8	2
2025	763	2	16	8	24	0	9	3

Table C-4 Container Crane Operational CO Emissions

Emission Factors taken from Nonroad Engine and Vehicle Emission Study Report PBN92126960, USEPA, Office of Mobile Sources, November 1991.

Year	Total Hours of Crane Operation (per year)	Container Crane (hp)	Load Factor (%)	CO Emission Factor (g/bhp-hr)	Annual CO Emissions (tons)	Change from Baseline (annual)
2003	3,256	725	43%	4.2	4.695	0.00
2005	3,434	725	43%	4.2	4.952	0.26
2008	3,599	725	43%	4.2	5.190	0.49
2010	3,750	725	43%	4.2	5.408	0.71
2015	4,144	725	43%	4.2	5.976	1.28
2020	4,579	725	43%	4.2	6.603	1.91
2025	5,060	725	43%	4.2	7.297	2.60

Horsepower (hp) is estimated for a 45 T (rated 40 long tons) dockside container crane 2 engines at 300 hp continuous rated (main hoist)

1 engine at 125 hp continuous rated (trolley travel motor)

g/bhp-hr = grams per boiler horsepower per hour

Table C-5 Yard Hostler Operational CO Emissions

Emission Factors taken from Nonroad Engine and Vehicle Emission Study Report PBN92126960, US EPA, Office of Mobile Sources, November 1991.

Year	Total Yard Hostler hours (per year)	Yard Hostler (hp)	Load Factor (%)	CO Emission Factor (g/bhp-hr)	Annual CO Emissions (tons)	Change from Baseline (annual)
2003	59,500	173	41%	2.8	13.014	0.00
2005	62,750	173	41%	2.8	13.725	0.71
2008	65,770	173	41%	2.8	14.386	1.37
2010	68,532	173	41%	2.8	14.990	1.98
2015	75,728	173	41%	2.8	16.564	3.55
2020	83,680	173	41%	2.8	18.303	5.29
2025	92,466	173	41%	2.8	20.225	7.21

Emission Factor (EF) is for off-highway diesel trucks

Note there are also emission factors for off-highway tractors: Load Factor = 65%, EF = 14.68 grams per boiler horsepower-hour

hp = horsepower g/bhp-hr = grams per boiler horsepower per hour

Table C-6 Truck and Privately Owned Vehicle Operational CO Emissions

Assumptions:

Travel through Maintenance Area is 10 miles roundtrip

	Total Annual Truck Emissions											
Year	Truck Trips (per year)	CO Emission Factor (grams/mile)	Average Roundtrip (miles)	Grams to Pounds	Total CO Emissions (tons)	Change from 2003						
2003	277,700	20.508	2,777,000	125,442.1	63	0						
2005	292,279	20.508	2,922,790	132,027.7	66	3						
2008	280,135	20.508	2,801,350	126,542.0	63	1						
2010	291,901	20.508	2,919,010	131,857.0	66	3						
2015	322,550	20.508	3,225,500	145,701.7	73	10						
2020	356,418	20.508	3,564,180	161,000.4	81	18						
2025	393,842	20.508	3,938,420	177,905.5	89	26						

	Total Annual POV Emissions											
Year	Auto Trips (per year)	CO Emission Factor (grams/mile)	Average Roundtrip (miles)	Grams to Pounds	Total CO Emissions (tons)	Change from 2003						
2003	303,576	20.508	3,035,760	137,130.8	69	0						
2005	319,488	20.508	3,194,880	144,318.5	72	4						
2008	335,088	20.508	3,350,880	151,365.3	76	7						
2010	370,032	20.508	3,700,320	167,150.1	84	15						
2015	408,408	20.508	4,084,080	184,485.3	92	24						
2020	450,840	20.508	4,508,400	203,652.6	102	33						
2025	497,640	20.508	4,976,400	224,793.0	112	44						

Table C-7 Proposed Action Total Construction Emissions

Construction Activity	Equipment Type	Number per Shift	Number of Days in Use	Hours of Operation per Shift	hp	Load	CO Emission Factors (g/bhp-hr)
	Tracked Dozer	1	70	16	160	57.5%	3.800
Demolition	Back Hoe	1	70	16	74	46.5%	6.800
	Dump Truck	3	70	16	489	41.0%	2.800
	Train	1	137	16		50.0%	
Transport of Fill	Barge	2	137	16		70.0%	
	Dump Trucks	160	9	16	489	41.0%	2.800
	Barge Pile Driver	1	128	10	325	62.0%	9.200
Deal Construction	Dock Dredgers	2	130	10	2,000	75.0%	
Dock Construction	Hopper Barge	2	130	10	2,000	70.0%	
	Tugboats	2	130	10	1,600	70.0%	
Compaction	Pile Driver	: 1	60	10	325	62.0%	9.200

hp = horsepower

g/bhp-hr = grams per boiler horsepower per hour

Total Cons	truction Emis Proposed A		lations
	Tons per Phase I	Duration	
Activity	Equipment Type	со	PM ₁₀
	Tracked Dozer	0.4316	
Demolition	Back Hoe	0.2889	
:	Dump Truck	2.0792	
	Train	0.6880	
Fill Transport	Barge	9.4512	,
	Dump Trucks	14.2574	
Fill	Operations		71.4000
	Barge Pile Driver	2.6156	
	Dock Dredgers	12.8700	
Dock Construction	Hopper Barge	#VALUE!	
	Tugboats	#VALUE!	
	Pile Driver	1.2261	r
	Trucks (travel)	0.3252	
Construction Travel	POVs (travel)	1.5810	
	Trucks (idle)	0.0149	
	TOTAL	#VALUE!	71.4000

POVs = Privately Owned Vehicles

Table C-8 Proposed Action - Construction Related Truck and Privately Owned Vehicle CO Emissions

Travel	CO Emission Factor (grams/mile)	Total Miles	Grams to Pounds	Total CO Emissions (tons) Maximum Construction Year
Truck (HDDV) ¹	20.508	14,400	650.4740088	0.325237004
POV (HBW local) ²	20.508	70,000	3,162.026432	1.581013216

^{&#}x27;Assumes 160 trucks/day for 9 days/10 miles round trip per truck

HDDV = Heavy Duty Diesel Vehicle

HBW = Home-Based Work

idle		CO Emission Factor Summer	Time	Summer Grams to Pounds	Total CO Emissions Summer (tons)
Truck (HDDV)	grams/hour	94		0.00000	0.00000
TIUCK (TIDDY)	grams/min	1.57	8,640	29.87841	0.01494

Assumes 6 minutes idle/truck/160 trucks per day/9 days

Table C-9 Proposed Action - Construction Related Locomotive CO Emissions

	motive Duty	-
	(lb/hr)	(gal/hr)
Line-haul	394	56
Switch	133	19

Assumptions:

Trains each have 3 locomotives

Travel through Maintenance Area is 14 miles of ARRC track

4 miles is within the yards with a speed limit of 10 mph, and is characterized by switch operation

137 days maximum year

10 miles is outside of the yards with an average speed of 40 mph

Each train idles for 20 minutes within the yard area per train movement

	Train Time in	Mode (hr	s/day)	Daily Fuel Consumption		CO Em		Annual	CO Em (tons)	nissions
	Train Movements per day	Switch	Line Haul	Switch	Line Haul	Switch	Line Haul	Switch	Line Haul	TOTAL
Construction Season	1	0.733	0.25	41.640	41.952	38.1	26.6	0.24	0.45	0.69

grams/gallon = g/gal

²Assumes 50 cars avg/140 days/10 miles round trip average per car

Sox

Table C-10 Proposed Action - Construction Related Fill and Dredging Emissions

Equipment Dock Dredgers								/:			L				Emissions (tons)
	5	(hp)	hours/day	days	total hrs	voc	8	NOx	PM 10	sox		VOC	00	NOx	PM 10
Je v	75%	2,000	12	260	3,120	0.0007	0.0055	0.0240	0.0007	0.0081		1.65	12.87	56.16	1.6
						E	ission Fa	Emission Factors (g/kw-hr) (Ref 2)	v-hr) (Ref	2)			Emiss	Emissions (tons)	Suc
Equipment	7	(hp)	hours/day	days	total hrs	NOC	03	NOx	PM 10	sox	200	VOC	00	NOx	PM 10
Transport Barge	%02	2,000	1	1	1,644	0.5000	5.0000	16.5000	0.2700	1		0.95	9.45	31.19	0.5
8	%02	1,600	1	-	2,600	0.5000		1		-		1.20	1	39.46	1
Dock Hopper Barges	%02	2,000	-	-	2,600	0.5000			16.5000 0.2700	1		1.49	150	49.33	-
Fill Operations m	months	acres	month-acre cubic yards	cubic yards	cubic yards		Emission	Emission Factors	PM ₁₀		TOTAL	2.85 No _x = N	2.85 24.83 95.62 No _x = Nitrous Oxides	95.62 cides	2
Construction Season	5.00	34.00	170.00	2 2 1 8 5 3 7 0 0	(by mousands) 2 2 18 54		a like	FIII TOTAL 71 4000	71 4000			2 1 200	Soc - Sullul Oxides	8	
The state of the s			e ye			lb/hp-hr = g/kwh = gr	pounds per	lb/hp-hr = pounds per horsepower hour g/kwh = grams per kilowatt hour	ver hour r						
ASSUMPTIONS: Av Tu	Average scow Tug trips 20 nautical milk Average speed 1 Kilowatt = Time for each of	Average scow capacity Tug trips 20 nautical miles for scow to dis Average speed 1 Kilowatt = Time for each disposal round tri Time for 2 has need as	Average scow capacity Tug trips 20 nautical miles for scow to disposal site Average speed 1 Kilowatt = Time for each disposal round trip		4,000 cubic yards 5 trips 40 nautical miles round trip 10 knots 1.341hp 4 hours 20 hours										

REFERENCES:

AP-42 Compilation of Air Pollutant Emission Factors, Chapter 3,4 Large Stationary Diesel and all Stationary Dual Fuel Engines, October 1996
 Final Regulatory Impact Analysis: Control of Emissions from Marine Diesel Engines, US EPA, November 1999. Table 3-3 Emissions Data from Baseline Category 2 Marine Diesel Engines
 Improvement of Specific Emission Factors (BACM Project No. 1). Final Report. Midwest Research Institue, Kansas City, MO. March 1996
Level 1, worst case scenario, emissions factor was applied for fill operations.

Table C-11 Total Construction Emissions for No-Action

Construction Activity	Equipment Type	No. per Shift	No. of Days in Use	Hrs. of Operation per Shift	Rated (hp)	Load	CO Emission Factors (g/bhp-hr)
	Tracked Dozer	1	160	16	160	57.5%	3.800
Demolition	Back Hoe	1	160	16	74	46.5%	6.800
	Dump Truck	3	160	16	489	41.0%	2.800
	Train	1	0	16		50.0%	
Transport of Fill	Barge	2	0	16		70.0%	
	Dump Trucks	160	0	16	489	41.0%	2.800
	Barge Pile Driver	1	180	12	325	62.0%	9.200
Dock Construction	Dock Dredgers	2	0	10	2,000	75.0%	1.25
Dock Construction	Hopper Barge	2	0	10	2,000	70.0%	***
	Tugboats	2	0	10	1,600	70.0%	w-v-w
Compaction	Pile Driver	1	0	10	325	62.0%	9.200

hp = Horsepower

g/bhp-hr = grams per boiler horsepower per hour

Total Coi	nstruction Emiss	ion Calcul	ations
	Tons per Phase C	uration	
Activity	Equipment Type	, co	PM ₁₀
	Tracked Dozer	0.9865	
Demolition	Back Hoe	0.6603	
	Dump Truck	4.7525	
	Train	0.6880	
Steel Transport	Barge	0.6899	
	Dump Trucks	0.0000	
Fill	Operations		0.0000
	Barge Pile Driver	4.4139	
Dock	Dock Dredgers	0.0000	
Construction	Hopper Barge	0.0000	
Conduction	Tugboats	0.0000	
	Pile Driver	0.0000	
Construction	Trucks (travel)	0.1016	4.5 j. 4.5
Travel	POVs (travel)	1.5810	11971
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Trucks (idle)	0.0299	
	TOTAL	14	0.0000

Table C-12 Construction Related Truck and Privately Owned Vehicle
CO Emissions for No-Action

Travel	CO Emission Factor (grams/mile)	Total Miles	Grams to Pounds	Total CO Emissions (tons)
Truck (HDDV) ¹	20.508	4,500	203.2731278	0.101636564
POV (HBWlocal) ²	20.508	70,000	3,162.026432	1.581013216

¹Assumes 160 trucks/day for 9 days/10 miles round trip per truck

HDDV = Heavy Duty Diesel Vehicle

HBW = Home Based Work

ldle		2005 CO Emission Factor Summer	Time	Summer Grams to Pounds	2005 Total CO Emissions Summer (tons)
Truck (HDDV)	grams/hour	94	selected in	0.00000	0.00000
Huck (HDDV)	grams/min	1.57	17280	59.75683	0.02988

Assumes 12 minutes idle/truck/50 trucks per day/9 days

Table C-13 Construction Related Locomotive CO Emissions for No-Action

	omotive Duty- Fuel Consum	
	(pounds/ hour)	(gal/ hour)
Line-haul	394	56
Switch	133	19

gal = gallon

Assumptions:

Trains each have 3 locomotives

Travel through Maintenance Area is 14 miles of ARRC track

4 miles is within the yards with a speed limit of 10 mph, and is characterized by switch operation

137 days in maximum year

10 miles is outside of the yards with an average speed of 40 mph

Each train idles for 20 minutes within the yard area per train movement

	7, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	me in Mo urs/day)	de	1			Emission Factor (grams/gal)		Annual CO Emissions (tons)	
	Train Movements per day	Switch	Line Haul	Switch	Line Haul	Switch	Line Haul	Switch	Line Haul	TOTAL
Construction Season	1	0.733	0.25	41.640	41.952	38.1	26.6	0.24	0.45	0.69

gal = gallon

²Assumes 50 cars avg/140 days/10 miles round trip average per car

Table C-14 Construction Related Fill and Dredging Emissions for No-Action

						Em	Emission Factors (lb/hp-hr) (Ref 1)	ctors (lb/	hp-hr) (Re	ef1)			Emiss	Emissions (tons)	E	-
Equipment	F	Rated	hours/day	days	total hrs	VOC	00	NOx	PM 10	sox		voc	00	NOX	4	PM 10
Dock Dredgers	75%	2,000	0	0	0	0.0007	0.0055	0.0240	0.0240 0.0007	0.0081		0.00	0.00	0.00		0.00
						Em	Emission Factors (g/kw-hr) (Ref 2)	ctors (g/l	cw-hr) (Re	f 2)	19		Emiss	Emissions (tons)	7	(SI
Equipment	5	Rated	hours/day	days	total hrs	voc	00	NOx	PM 10	sox		VOC	00	NOx	0	PM 10
Transport Barge	%02	2,000	12	10	120	0.5000	5.0000	16.5000	0.2700	-		0.07	0.69	2.28		0.04
Dock Tug Boats	%02	1,600	-	1	0	0.5000		16.5000		1	× .	0.00	0.00	0.00	1	0.00
Dock Hopper Barges	%02	2,000	-	-	0	0.5000		16.5000	5.0000 16.5000 0.2700	-		0.00	0.00	0.00	1	0.00
Fill Operations	months	acres	month-acre	cubic yards	cubic yards (by thousands)		Emission Factors	ion Factors	PM ₁₀		TOTAL	0.00 No _x = N So _x = S	0.00 0.00 0.00 No _x = Nitrous Oxides So _x = Sulfur Oxides	0.00 xides	_	0.00
Construction Season	00.0	34.00	0.00	2218537.00	2218.54		iii.	FIII TOTAL	0.0000	i i i						
LF = Load Factor																
hp = horsepower						lb/hp-hr g/kwh =	lb/hp-hr = pounds per horsepower per hour g/kwh = grams per kilowatt hour	er horsepo r kilowatt	wer per hor	5						
ASSUMPTIONS:	Average scow capacity Tug trips	scow cap	pacity		4,000 cubic yards 5 trips											
	ZU nautical miles for sco Average speed 1 Kilowatt = Time for each disposal r Total tug time for 2 tugs	speed speed t = each disp	to nautical miles for scow to disp. Average speed Kilowatt = Time for each disposal round trip Total tug time for 2 tugs per day	w to disposal site round trip per day	40 nautical miles round trip 10 knots 1.341 hp 4 hours 20 hours	dut fub										
REFERENCES:	1) AP-42 2) Final R Catego 3) Improv Level	AP-42 Compilation of Final Regulatory Imp Category 2 Marinee E mprovement of Spec Level 1, worst case	AP-42 Compilation of Air Pollutant E Final Regulatory Impact Analysis: C Category 2 Marinee Diesel Engines Improvement of Specific Emission F Level 1, worst case scenario, emis	lutant Emissior lysis: Control or ngines ssion Factors (5, emissions fac	1) AP-42 Compilation of Air Pollutant Emission Factors, Chapter 3,4 Large Stationary Diesel and all Stationary Dual Fuel Engines, October 1996 2) Final Regulatory Impact Analysis: Control of Emissions from Marine Diesel Engines, US EPA, November 1999. Table 3-3 Emissions Data from Baseline Category 2 Marinee Diesel Engines 3) Improvement of Specific Emission Factors (BACM Project No. 1). Final Report. Midwest Research Institue, Kansas City, MO. March 1996 Level 1, worst case scenario, emissions factor was applied for fill operations.	4 Large Station ine Diesel Eng Final Report. Il operations.	iary Diesel ines, US E Midwest	and all S PA, Nove Research	tationary I ember 199	Dual Fuel E 9. Table S Kansas Cit	Engines, 3-3 Emis ty, MO.	October sions Da March 19	r 1996 ata from 996	Baselin	ø.	

APPENDIX D

NOISE

APPENDIX D NOISE

This appendix describes the approach to the noise analysis for the Marine Terminal Redevelopment EA. The approach consists of tracking the noise levels through different phases of the Project at eight specific points of interest. Tracking the noise at each of the specific points included determining the baseline noise levels, noise levels generated through the different phases of construction, and the noise level when the POA is in full operation in 2025. Baseline noise measurements were made in June 2004 to quantify the existing noise levels. These noise levels were used in the modeling process to compute the incremental changes resulting from the proposed action and to assess the impact at each of the sites chosen for the analysis.

There were four parts to the noise analysis: 1) the identification of noise- and vibration-sensitive land uses surrounding the Project area; 2) the quantification of the baseline noise and vibration levels at each of the sites identified; 3) the development of an inventory of the noise sources resulting from the Project; and 4) the determination of the expected noise and vibration impacts at each of the sites. The inventory consisted of the number and location of each of the sources, the expected periods of operation during each phase of the Project, and the reference noise level for each noise source measured at some quantifiable distance, typically 50 feet, from the source. The analysis considered propagation effects such as spherical spreading, ground absorption, and the effect of acoustic barriers that could result from buildings or topographic features. The expected noise levels were compared to the baseline noise levels to determine the severity of the impact. Any sites identified falling within the criteria of severe impact were analyzed to determine viable methods to reduce the noise level.

Noise Metrics Used in Analysis

The two primary noise metrics used in the analysis were the *hourly equivalent sound level* (Leq(1)) and the *day-night average sound level* (Ldn). Both metrics are denoted as dBA. The letter "A" indicates that the sound level has been A-weighted, which means the sound has been filtered to reduce low frequency and high frequency sounds similar to the way the human ear filters sound frequencies. Without the A-weighting, the sound levels reported in this report could represent sound levels that people cannot hear. A-weighted sound levels were used because they accurately characterize the expected sound level for this Project and can be used to determine the associated impacts.

The hourly equivalent sound level (Leq(1)) describes the noise events averaged over a 1-hour period in time. This metric was used to analyze noise sensitive land uses including tracts of land where quiet is an intended purpose for the land use. Some examples include outdoor amphitheaters, national historic landmarks, and parks. Another application of this metric was in situations where it is important to avoid activity interference such as schools, libraries, and churches.

The Ldn describes a noise exposure averaged over a 24-hour period, with noise events between 10 p.m. and 7 a.m. increased by ten decibels (or dB) to account for the greater nighttime sensitivity to noise when people are sleeping. This metric was used in the analysis of residential areas (apartment complexes, residential suburbs, and hospitals).

Description of Analysis Methodology

The very nature of transit projects often necessitates locating the Project area close to a concentration of people in urban areas. Noise and vibration is always a concern with these projects during the planning stages through the development phases, and to the final implementation phase of the project. The FHWA and FTA have developed a standard procedure for the analysis of the impacts. This procedure is described below with adaptation to this specific Project's needs.

Identification of Noise and Vibration Sensitive Land Uses

The first phase of the noise analysis was the identification of noise sensitive land uses. Initial screening for noise-sensitive sites began with maps that show land use near the POA. From these maps, initial sites were chosen for the analysis. Eight locations were chosen for the noise study, including four at the POA and four within the nearby residential areas—two at Cherry Hill housing on Elmendorf AFB and two on Government Hill. Locations of these properties are presented in section 3.2.2 of the EA.

Quantification of the Existing Noise Environment

The intent of the baseline noise measurements was to measure the ambient background noise levels, which are the sounds that are heard without noise resulting from identifiable sources. Identifiable sources could be traffic noise, barking dogs, factory noise, or children at play. Baseline noise levels were made over a continuous 24-hour period at each of the specific points. The noise metrics included a 1-hour Leq, Ldn, Lmax, L1, L10, L50, L33, L90, and L99. All noise metrics were reported as A-weighted sound levels. The measurements were made during calm atmospheric conditions, when the wind speeds were reported to be less than ten knots, and when there were no adverse weather conditions such as rain, sleet, or snow.

Noise measurements were made in open areas where there are no hard reflecting surfaces such as buildings or cliffs. A noise expert visited each site at different times in the day to verify that there was no unusual human activity that might suddenly appear during the measurement phase. If any occurred, it was noted.

Inventory of Noise Sources for Impact Analysis

An inventory of equipment was developed based on the major construction activities (i.e. dredging, filling, paving, demolition). The types of noise sources included in the inventory were all transit modes, all construction operations, and all fixed facilities that could accompany the proposed action. It was

important to consider all of the sources because an equivalent noise level can result from a single source that produces a high noise level or multiple lower noise sources acting together. The hourly equivalent sound level and the day-night average sound level are noise metrics with an integration period of 1 hour and 24 hours, respectively. Any calculations involving these metrics require specific definition on the number of pieces of equipment, the expected periods of operation during each phase of construction, and the frequency of use.

Sound levels for construction equipment are reported as either sound pressure level at a specific distance, or as sound power level. For consistency purposes, sound pressure level was used for all source level definition (Tables D-1 to D-5).

Determination of Expected Noise Levels

Noise calculations were based on standard acoustical techniques for propagating sound levels in urban areas. The calculations included spherical spreading, air absorption, ground attenuation, screening from buildings and barriers, and topographic effects. The calculations assumed standard atmospheric conditions during the summer months when people are more active outdoors. Results for Alternatives A, B, C, and No Action are presented in Table D-6.

The noise impact criteria used in Table D-6 are applied to transportation related projects to define when a project could have adverse effects on the community. Generally, there are three levels of impact: no impact, impact, and severe impact. The FTA noise impact criteria are included as Figure D-1. Each noise study site was individually evaluated using these criteria to determine the expected level of impact, given its type of land use. For this analysis, an increase in noise levels 2.5 dBA or more above baseline in Category 2 or 3 areas was considered to be an impact. Based on baseline noise levels and the estimated noise level derived from this analysis, there would be no adverse affects to residential areas or parks from construction activities for Alternatives A, B, and C. There would be an adverse impact to residential areas and parks under the no-action alternative.

Mitigation

If an impact is found to be severe, a detailed analysis is performed to determine the exact cause for the impact to develop corrective actions to reduce the severity. Often noise from transportation-related projects can be reduced at the source using sound attenuation techniques. However, in the POA noise study, no impacts resulted from construction or operations under any of the design alternatives. Noise impacts under the no-action alternative could be mitigated through the construction of sound barriers during pile driving.

Table D-1 Sound Levels During Construction - Alternative A

			d Levels of			7P111		ance in	feet from	n source	F	
Description	Number of vehicles	Horsepower	Power (kilowatts)	Sound Power (dBA)	50	100	500	1,000	2,000	3,000	4,000	5,000
Pile Driver	1	NA	NA	130	95	88	70	63	55	51	48	45
Grader, wheeled	1	300	223.5	111	76	69	51	44	36	32	29	26
Truck, wheeled	2	300	223.5	111	79	72	54	47	39	35	32	29
Bulldozer, tracked	1	300	223.5	111	76	69	51	44	36	32	29	26
Trencher, wheeled	1	300	223.5	111	76	69	51	44	36	32	29	26
Backhoe, wheeled	1	250	186.25	110	75	68	50	43	35	31	28	25
		Total Lev	el Leq, dBA		96	88	71	63	56	51	48	46
		Night - assume ours per day of			94	86	69	61	54	49	46	44

						Dista	ance in	leet fron	n source	3	
Number Locomotives	Number of Cars	Trains per Day	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000
2	80	1	15	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6
		Total Leve	Leq, dBA	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6
Total	Day/Night - as	sume no nigl	httime ops	48	43	33	28	24	21	19	18

Assumes Jointed Track with no barriers or obstructions

Cars and Trucks

	,				Dist	ance in 1	feet fron	n source	Ē	
Description	Number of Vehicles per hour	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000
Cars	10	30	41.2	36.7	26.2	21.7	17.1	14.5	12.6	11.2
Trucks	35	30	58.6	54.1	43.6	39.1	34.6	31.9	30.1	28.6
	Total Leve	Leq, dBA	59	54	44	39	35	32	30	29
	iht - assume no nighttime ops s per day of traffic operations.	16	57	52	42	37	33	30	28	27

					Dist	ance in t	eet fron	n source	Ē	
Number of Ships	Average Day Hours	Average Night Hours	50	100	500	1,000	2,000	3,000	4,000	5,000
6	12	0	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
	Total Leve	l Leq, dBA	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
Day-Night Av	erage Sound	Level, dBA	75.2	67.7	50.2	42.7	35.2	30.8	27.6	25.2

Table D-2 Sound Levels During Construction - Alternative B

		Sound	Levels of 0	Construct	ion Ec	uipme						
							Dist	ance in	eet fron	n source	9	
Description	Number of vehicles	Horsepower	Power (kilowatts)	Sound Power (dBA)	50	100	500	1,000	2,000	3,000	4,000	5000
Pile Driver	1	NA	NA	136	101	94	76	69	61	57	54	51
Grader, wheeled	1	300	223.5	111	76	69	51	44	36	32	29	26
Truck, wheeled	2	300	223.5	111	79	72	54	47	39	35	32	29
Bulldozer, tracked	1	300	223.5	111	76	69	51	44	36	32	29	26
Trencher, wheeled	1	300	223.5	111	76	69	51	44	36	32	29	26
Backhoe, wheeled	1	250	186.25	110	75	68	50	43	35	31	28	25
		Total Leve	l Leq, dBA		101	94	76	69	61	57	54	51
	1 ' '	ght - assume n s and 10 hour construction	s per day of	16	100	92	75	67	60	55	52	50

						Dist	ance in 1	feet fron	n source	3	
Number Locomotives	Number of Cars	Trains per Day	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000
2	80	1	15	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6
	4	Total Level	Leq, dBA	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6
Total Day/I	Vight - assum	е по nighttin	ne ops	48	43	33	28	24	21	19	18

Assumes Jointed Track with no barriers or obstructions

Cars and Trucks

					Dist	ance in 1	eet fron	n source	}	
Description	Number of Vehicles per hour	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000
Cars	10	30	41.2	36.7	26.2	21.7	17.1	14.5	12.6	11.2
Trucks	35	30	58.6	54.1	43.6	39.1	34.6	31.9	30.1	28.6
	Total Leve	Leq, dBA	59	54	44	39	35	32	30	29
	ght - assume no nighttime 10 hours per day of traffic operations.	16	57	52	42	37	33	30	28	27

					Dist	ance in 1	eet fron	n source)	
Number of Ships	Average Day Hours	Average Night Hours	- 50	100	500	1,000	2,000	3,000	4,000	5,000
6	12	0	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
1.65	Total Leve	l Leq, dBA	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
Day-Night Ave	rage Sound	Level, dBA	75.2	67.7	50.2	42.7	35.2	30.8	27.6	25.2

Table D-3 Sound Levels During Construction - Alternative C

		Sound	Levels of C	Construct	ion Ec	luibme	ent					
							Dist	ance in	eet fron	n source	9	
Description	Number of vehicles	Horsepower	Power (kilowatts)	Sound Power (dBA)	50	100	500	1,000	2,000	3,000	4,000	5,000
Pile Driver	1	NA ·	NA	130	95	88	70	63	55	-51	48	45
Grader, wheeled	1	300	223.5	111	76	69	51	44	36	- 32	29	26
Truck, wheeled	2	300	223.5	111	79	72	54	47	39	35	32	29
Bulldozer, tracked	1	300	223.5	111	76	69	51	44	36	32	29	26
Trencher, wheeled	1	300	223.5	111	76	69	51	44	36	32	29	26
Backhoe, wheeled	1	250	186.25	110	75	68	50	43	35	31	28	25
		Total Lev	el Leq, dBA	***************************************	96	- 88	71	63	56	51	48	46
		ght - assume i ps and 10 hou construction	rs per day of	16	94	86	69	61	54	49	46	44

						Dista	ance in	eet fron	n source	9	
Number Locomotives	Number of Cars	Trains per Day	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000
2	80	1	15	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6
		Total Leve	l Leq, dBA	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6
Total D	ay/Night - as:	sume no nigl	nttime ops	48	43	33	28	24	21	19	18

Assumes Jointed Track with no barriers or obstructions

Sars and Trucks

					Dist	ance in 1	eet fron	n source	3	
Description	Number of Vehicles per hour	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000
Cars	10	30	41.2	36.7	26.2	21.7	17.1	14.5	12.6	11.2
Trucks	35	30	58.6	54.1	43.6	39.1	34.6	31.9	30.1	28.6
	Total Level Leg, dBA				44	39	35	32	30	29
Total Day/Night - assume no nighttime ops and 16 hours per day of traffic 16 operations.			57	52	42	37	33	30	28	27

					Dista	ance in	feet fron	n source	3	
Number of Ships	Average Day Hours	Average Night Hours	50	100	500	1,000	2,000	3,000	4,000	5,000
6	12	. 0	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
 à	Total Leve	l Leq, dBA	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
Day-Night Average Sound Level, dBA					50.2	42.7	35.2	30.8	27.6	25.2

Table D-4 Sound Levels During Operations

		Sou	nd Levels o	f Operati	ons E	quipm	ent					
		4. 1					Dist	ance in	feet fron	n source	е	
Description	Number of vehicles	Horsepower	Power (kilowatts)	Sound Power (dBA)	50	100	500	1,000	2,000	3,000	4,000	5,000
Pile Driver	0.001	NA	NA	130	65	58	40	33	25	21	18	15
Grader, wheeled	0.001	300	223.5	111	46	39	21	14	6	2	-1	-4
Truck, wheeled	0.001	300	223.5	111	46	39	21	14	6	2	-1	-4
Bulldozer, tracked	0.001	300	223.5	111	46	39	21	. 14	6	2	-1	-4
Trencher, wheeled	0.001	300	223.5	111	46	39	21	14	6	2	-1	-4
Backhoe, wheeled	0.001	250	186.25	110	45	38	20	13	5	1	-2	-5
	Total Level Leg, dBA				66	58	41	33	26	21	18	16
	Total Day/Ni or		42	34	17	9	2	-3	-6	-8		

Number Locomotives Number of Cars Trains per Day Speed (mph) 50 100 500 1,000 2,000 2 50 2 15 63.9 59.4 48.9 44.4 39.8			
	3,000	4,000	5,000
	37.2	35.3	33.9
Total Level Leq, dBA 63.9 59.4 48.9 44.4 39.8	37.2	35.3	33.9
Total Day/Night - assume no nighttime ops 50 46 35 31 26	23	22	20

Assumes Jointed Track with no barriers or obstructions

Cars and Trucks

			Distance in feet from source									
Description	Number of Vehicles per hour	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000		
Cars	160	30	53.2	48.7	38.2	33.7	29.2	26.5	24.7	23.2		
Trucks	215	30	66.5	62.0	51	47.0	42.5	39.8	37.9	36.5		
Total Level Leg, dBA			67	62	52	47	43	40	38	37		
Total Day/Night - assume no nighttime ops and 10 hours per day of traffic 10 operations.				58	48	43	39	36	34	33		

			Distance in feet from source								
Number of Ships	Average Day Hours	Average Night Hours	50	100	500	1,000	2,000	3,000	4,000	5,000	
4	10	0	76.5	68.9	51.5	43.9	36.4	32.0	28.9	26.5	
	Total Level Leq, dBA				51.5	43.9	36.4	32.0	28.9	26.5	
Day-Night Average Sound Level, dBA				65.6	48.1	40.6	33.0	28.6	25.5	23.1	

Table D-5 Sound Levels During Construction - No-Action Alternative

		Sound	Levels of C	Construc	tion E	quipm	nent					
	18						Distar	ice in fe	et from	source		***************************************
Description	Number of vehicles	Horsepower	Power (kilowatts)	Sound Power (dBA)	50	100	500	1,000	2,000	3,000	4,000	5,000
Pile Driver	1	NA	NA	130	95	88	70	63	55	51	48	45
Grader, wheeled	1	300	223.5	111	76	69	51	44	36	32	29	26
Truck, wheeled	2	300	223.5	111	79	72	54	47	39	35	32	29
Bulldozer, tracked	1	300	223.5	111	76	69	51	44	36	32	29	26
Trencher, wheeled	1	300	223.5	111	76	69	51	44	36	32	29	26
Backhoe, wheeled	1	250	186.25	110	75	68	50	43	35	31	28	25
		Total Lev	vel Leq, dBA		96	88	71	63	56	51	48	46
	Total Day/Night - assume no nighttime ops and 10 hours per day of construction operations.				94	86	69	61	54	49	46	44

					Distance in feet from source									
Number Locomotives	Number of Cars	Trains per Day	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000			
2	80	1	15	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6			
		Total Level	Leq, dBA	61.6	57.1	46.6	42.1	37.6	35.0	33.1	31.6			
Total Day/Night - assume no nighttime ops				48	43	33	28	24	21	19	18			

Assumes Jointed Track with no barriers or obstructions

ars and Trucke

			Distance in feet from source 50 100 500 1,000 2,000 3,000 4,000 5,000									
Description	Number of Vehicles per hour	Speed (mph)	50	100	500	1,000	2,000	3,000	4,000	5,000		
Cars	10	30	41.2	36.7	26.2	21.7	17.1	14.5	12.6	11.2		
Trucks	35	30	58.6	54.1	43.6	39.1	34.6	31.9	30.1	28.6		
	Total Level	Leq, dBA	59	54	- 44	39	35	32	30	29		
Total Day/Nigh and 16 hours p		57	52	42	37	33	30	28	27			

				1.	Distan	ce in fe	et from	source		
Number of Ships	Average Day Hours	Average Night Hours	50	100	500	1,000	2,000	3,000	4,000	5,000
6	12	0	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
	Total Level	Leq, dBA	78.2	70.7	53.2	45.7	38.2	33.8	30.7	28.2
Day-Night Average Sound Level, dBA				67.7	50.2	42.7	35.2	30.8	27.6	25.2

Table D-6 Results for Alternatives

				Model Noise So	ources During C	Model Noise Sources During Construction Alternative A	rnative A			
Site	Measurement Site	Continous or Spot	Baseline	Construction	Rail	Cars and	Ships	Total	Increase in	Impact
Number	Description	Measurements	(Ldn)	Noise (Leg [24])	(Led [24])	rucks (Leg [24])	(Leq [24])	Noise (Ldn)	Noise Level	Critera
	Port Northern Berth	Spot	02	80	57	52	71	80.9	10.9	No Impact
	Dort Building	Continous								
	Observation Dools	88 hours round 1 and	99	8	25	\$	71	80.7	14.7	No Impact
2	Observation Deck	49 hours round 2								
3	Port Sourthern Berth Spot	Spot	75	80	57	54	71	81.6	6.6	No Impact
4	Corner of Termina	Spot	02	29	46	41	53	71.8	1.8	No Impact
	Coverament Hill!	Continous								
	Maker Deak	55 hours round 1 and	63	26	40	37	40	63.8	0.8	No Impact
5	Michay Park	49 hours round 2							}	
9	Brown's Point Park	Spot	09	75	38	36	38	61.0	1.0	No Impact
	Cherry Hill Housing,		J. O	Ç		1	į,			
7	North End	Spot	6	00	04	37	04	65.5	6.0	No Impact
	Chorny Hill United	Continous								
	Criefly mill mousing,	South Cad	အ	75	38	32	38	63.5	0.5	No Impact
8	South Elia	49 hours round 2								

				Madel Major C.	C comment	A14	2			
				e asion tanous	Jurges During	model noise sources puring construction Alternative B	rnauve o			
Site	Measurement Site	Continue or Snot	Baseline	Construction	Rail	Cars and	Ships	Total	Increase in	Impact
Number		Measurements	(Ldn)	Noise (Leq [24])	(Leq [24])	Trucks (Leg [24])	(Leq [24])	Noise (Ldn)	Noise Level (dB)	Critera
1	Port Northern Berth	Spot	70	83	- 57	54	71	83.5	13.5	No Impact
C	Port Building,	Continous	90	CO	£7	70	7	5		
7	Observation Deck	49 hours round 2	00	CO)C	š	7	4.50	4.71	No impact
3	Port Sourthern Berth	Spot	75	83	57	75	71	83.9	8.9	No Impact
4	Corner of Termina	Spot	70	1.1	46	41	53	73.6	3.6	No Impact
	Conformant Lill/	Continous								
3	McKay Park	55 hours round 1 and	63	61	40	37	40	65.2	2.2	No Impact
		49 nours round 2								
6		Spot	60	58	.38	36	38	62.2	2.2	No Impact
7	Cherry Hill Housing, North End	Spot	65	61	40	37	40	66.5	1.5	No Impact
-		Continous					1 1 1 1 1 1 1 1 1			
∞	Circlity Initial Doubling, 24 hours r	24 hours round 1 and	8	28	38	35	38	64.2	1.2	No Impact
	South Ella	49 hours round 2			,					


Table D-6 Results for Alternatives - (con't)

				Model Noise So	ources During C	Model Noise Sources During Construction Alternative C	rnative C			
Site Number	Measurement Site Description	Continous or Spot Measurements	Baseline (Ldn)	Construction Noise (Leg [24])	Rail (Leq [24])	Cars and Trucks	Ships (Leq [24])	Total Noise	Increase in Noise Level	Impact Critera
1	Port Northern Berth	Spot	70	80	57	54	71	80.9	10.9	No Impact
2	Port Building, Observation Deck	Continous 88 hours round 1 and 49 hours round 2	99	. 08	57	54	71	80.7	14.7	No Impact
3	Port Sourthern Berth Spot	Spot	75	80	57	54	71	81.6	6.6	No impact
4	Corner of Termina	Spot	70	29	46	41	53	71.8	1.8	No Impact
က	Government Hill/ McKay Park	Continous 55 hours round 1 and 49 hours round 2	63	56	40	37	40	63.8	0.8	No Impact
9	i i	Spot	9	54	38	36	38	61.0	1.0	No Impact
7	Cherry Hill Housing, North End	Spot	65	99	40	37	40	65.5	0.5	No Impact
8	Cherry Hill Housing, South End	Cherry Hill Housing, 24 hours round 1 and South End 49 hours round 2	63	54	38	35	38	63.5	0.5	No Impact

				Model Noise Sources During Construction No-Action Alternative	es During Cons	truction No-Actic	on Alternative			
Site Number	Measurement Site Description	Continous or Spot Measurements	Baseline (Ldn)	Construction Noise (Leq [24])	Rail (Leq [24])	Cars and Trucks (Leq [24])	Ships (Leq [24])	Total Noise (Ldn)	Increase in Noise Level (dB)	Impact Critera
-	Port Northern Berth	Spot	20	85	42	44	09	85.1	15.1	No Impact
2	Port Building, Observation Deck	Continous 88 hours round 1 and 49 hours round 2	99	80	42	44	09	80.2	14.2	No Impact
3	ţ	Spot	75	76	42	44	9	78.6	3.6	No Impact
4	Corner of Termina	Spot	70	9/	43	48	54	77.0	7.0	No Impact
5	Government Hill/ McKay Park	Continous 55 hours round 1 and 49 hours round 2	63	63	38	37	39	0.99	3.0	Impact
9	Brown's Point Park	Spot	09	62	38	36	36	64.1	4.1	Impact
7	Cherry Hill Housing, North End	Spot	65	63	42	37	39	67.1	2.1	No Impact
8	Contin Cherry Hill Housing, 24 hou South End 49 hou	Continous 24 hours round 1 and 49 hours round 2	63	62	42	36	39	65.6	2.6	Impact

Table D-6 Results for Alternatives - (con't)

				Model Nois	se Sources Dur	Model Noise Sources During Operatopms 2025	2025	됩 [†]		
Site	Measurement Site	Continuis or Snot	Receline	Construction	lied	Cars and	China	Total	Increase in	1000
Number		Measurements		Noise	(Leg [24])	Trucks	(Leg [24])	Noise	Noise Level	Critera
				(Leg [24])	4	(Leg [24])	7	(Ldn)	(dB)	
	Port Northern Berth	Spot	02	0	49	52	51	70.2	0.2	No Impact
	Port Building	Continous					100			
7	Observation Deck	88 hours round 1 and	99	0	49	52	51	66.4	4.0	No Impact
	Observation Deck	49 hours round 2								
3	Port Sourthern Berth Spot	Spot	75	0	44	52	51	75.0	0.0	No Impact
4	Corner of Termina	Spot	02	0	44	52	4	70.1	0.1	No Impact
	Covernment Uill/	Continous					1957 1957			
2	MoKay Dark	55 hours round 1 and	63	0	38	49	36	63.2	0.2	No Impact
	MIChay rain	49 hours round 2								
9	Brown's Point Park	Spot	09	0	36	43	뙁	60.1	0.1	No Impact
7	Cherry Hill Housing, North End	Spot	. 99	0	38	46	36	65.1	0.1	No Impact
	3	:								
	Cherry Hill Housing	Continous						\$ \$ \$		
Φ	South End	24 hours round 1 and	ဗ	0	36	.	ਲ	63.1	0.1	No Impact
		49 hours round 2								



(Source: FTA guidance manual, Figure 3-1)

APPENDIX E

HYDRODYNAMICS

Tidal Circulation Modeling Study To Support the Port of Anchorage Expansion

Bruce Ebersole and Layla Raad

Sponsored by USACE Alaska District

U.S. Army Engineer Research and Development Center's Coastal and Hydraulics Laboratory Located at the Waterways Experiment Station, Vicksburg, Mississippi

May 2004

APPENDIX E HYDRODYNAMICS

Introduction

The Port of Anchorage (POA) is planning a major expansion program that will occur over approximately the next 7 years. The objective of this study is to apply an existing hydrodynamic circulation model of upper Cook Inlet and the POA vicinity to characterize tidal circulation patterns at and near the Port for two conditions: existing conditions and a condition that represents the proposed complete expansion of the Port infrastructure. The hydrodynamic model applied here is currently being upgraded in support of work being done by the U.S. Army Corps of Engineers, Alaska District, to investigate sedimentation at the Port. The model enhancement program is ongoing, and the model in its present state of development was used to conduct this study.

Accuracy of the upgraded model was checked for this study, simply by comparing calculated water level values to measured water levels at National Oceanic and Atmospheric Administration (NOAA) stations. A significant amount of model validation was previously performed using measured current data for upper Cook Inlet, but for a model grid that had a regional focus (not a local, Port focus). That prior work has been extensively documented. Measurements indicated that in certain parts of upper Cook Inlet there is significant three-dimensional structure to the current fields, particularly in the gyres formed by strong flows past headlands, and deeper areas of the inlet gorge. Flows on the tidelands are expected to have less vertical structure, although current measurements there are rather sparse. Model enhancement and validation (involving comparison of model results with measured current data collected right at the Port) are continuing. This work is being funded by the District, but it will not be completed until late summer 2004. The purpose of additional validation work is to investigate model skill in predicting velocity conditions right at the Port, and in the gyre shed by Cairn Point, which most strongly influences currents at the Port. Calculated results presented in this study reflect those from a two-dimensional, depthaveraged model. The horizontal velocity structure of the gyres seems to be predicted reasonably well with the present model, at least qualitatively. But accuracy of flow field details right at the Port, and in the gyre near the Port, is less certain at this time.

Model simulation for a neap-spring tidal cycle during August 2002 was conducted with and without the proposed expansion. The model was forced with tidal constituents along its ocean boundary (which is seaward of Kodiak Island) and river flow at the locations where major freshwater discharges enter Upper Cook Inlet. Time series of water level and current speed and direction at selected stations in the study area were examined to assess the impact of the expansion on the tidal circulation. Also, circulation patterns in the port vicinity and surrounding area, were studied with and without the proposed expansion using a number of graphical display products and animations.

The influence of the proposed port expansion on flow and circulation in the region was examined; and a preliminary, cursory assessment of the impact of the port expansion on circulation and sedimentation in the harbor was made. Those results are documented here.

Previous Model

Cook Inlet lies between 59° and 61° 30′N latitude and 149° and 154° W longitude and covers more than 26×10^3 km². This large tidal estuary flows into the Gulf of Alaska and has an average depth of 100 m (Raney 1993). As reported by the U.S. Coast and Geodetic Survey in 1969, Cook Inlet has the tenth highest mean spring tidal range in the world with a value of 10 m recorded for the Turnagain Arm (Raney 1993). Significant portions of Knik and Turnagain Arms are exposed at low tide. Several extensive tidelands are located in the upper Cook Inlet. Of the many rivers that discharge into the Inlet, three contribute about 70% of its total freshwater input. These are the Knik, Matanuska, and Susitna Rivers (Mulherin *et al.* 2001). Four rivers were considered in the model: the Knik, Matanuska, Susitna and Kenai rivers.

The Advanced CIRCulation hydrodynamic (ADCIRC-2DDI) model (Luettich, Westerink, Scheffner 1992) was used to evaluate the circulation pattern in the upper Cook Inlet area. Model water-surface and depth-averaged current data were examined and the accuracy of the model results was evaluated by comparing it to measured water level and current data collected during 2002.

ADCIRC is a system of computer programs for solving time dependent, varying free surface, circulation, and transport problems in two horizontal dimensions. These programs utilize the finite element method in space and therefore can be run on highly flexible, irregularly spaced grids. Fine resolution can be specified in the area of interest and coarse resolution can be specified in areas distant from the region of interest. Model accuracy is directly related to the ability to resolve shorelines and topographic features, and ADCIRC's unstructured grid system allows this to be done well. Model simulations included forcing with tidal constituents and river flow. The ADCIRC finite element grid domain included Cook Inlet and part of the Gulf of Alaska as seen in Figure 1.

The grid coastline was chosen in a geographic range defined by longitude of 157°-148.5° W and latitude of 55°-63° N. The coastline was extracted using NOAA Coastline Extractor. The digitized shoreline coordinates were obtained from the World Vector Shoreline (WVS). Shoreline data are based on Mean High Water (MHW) and is referenced to World Geodetic System (WGS 84).

The ADCIRC finite element grid is shown in Figure 2 with coarse resolution over the open ocean and increasing resolution toward the Port of Anchorage in upper Cook Inlet. Element areas vary greatly over the computational domain, with the ratio of the offshore element to the smallest element in the Anchorage




Figure 1 ADCIRC Domain




Figure 2 ADCIRC Grid

area being 8.5×10^4 . Grid resolution can vary spatially, and grading between coarse and fine resolution should be done with regard to transition between element areas. A general rule is that adjacent elements should not differ in size by more than 50 percent (Donnell *et al.* 1996). More resolution was added to the study with finest node spacing of about 70 m near the Port of Anchorage as shown in Figure 3. The number of nodes and elements of the mesh were 26,841 and 50,448 respectively.




Figure 3 Details of ADCIRC Grid for the Port of Anchorage Area

The ADCIRC-2DDI model was developed to simulate regional-scale processes, with emphasis on simulating water surface elevation and current speed and direction in the upper Cook Inlet, with less emphasis on the immediate vicinity of the Port. Field measurements were conducted during 34 days in 2002 at fixed locations and also along transects during different tidal cycles to assess model skill in simulating regional scale hydrodynamic processes. The field measurements were used to characterize the current in the upper Cook Inlet and to evaluate the accuracy of the 2-D model in the area. That work has been extensively documented.

The two-dimensional ADCIRC model was capable of reproducing the details of the current field in the study area extending from just south of Fire Island to Cairn Point, when and where eddies were not present and also for areas of mild vertical current structure. Some of the eddies were captured qualitatively, with uncertain quantitative accuracy. To support detailed hydrodynamic and sedimentation studies at the Port, additional model refinement was needed, as well as more validation to currents right at the Port, and that work is ongoing.

Model Upgrade

The ADCIRC model required upgrading to address issues of sedimentation at the port, and this type of upgrade was needed to be able to accurately evaluate the impacts of the proposed Port of Anchorage Marine Terminal Expansion. The ADCIRC model upgrade included the following tasks:

- Improve representation of the irregular shoreline and structures in the port area and along the inlet shoreline between Cairn Point and Point Woronzof.
- Incorporate available depth survey data in the port vicinity closest to the model simulation time.
- Improve the representation of the tidal flat elevations along the shoreline between Cairn Point and Point Woronzof. Also, upgrade the tidal flat elevation in some areas of Susitna and Turnagain tidelands (to come later this summer). Previous work confirmed the importance of accurately representing the tidal flat elevations in the model.
- Reference upgraded grid depths to ADCIRC datums.
- Increase grid resolution in the port vicinity.
- Improve grid quality in the study area.

Improve Representation of Irregular Shoreline

Define New Shoreline

The original digitized shoreline of the ADCIRC grid was obtained from the WVS. This shoreline was used in the original model development. Shoreline data are based on MHW referenced to Mean Low Low Water (MLLW). This was a crude representation of the shoreline in the port vicinity, as shown in Figure 4.

To better resolve the shoreline, aerial imagery with 3-ft pixel resolution was obtained for the shoreline between Cairn Point and Point Woronzof. The date of the imagery was September 10, 2002 and the time was 20:06-22:26 GMT. The imagery was acquired in a registered .tiff format and its projection was Alaska State Plane, Zone 4. The horizontal datum was NAD 27 and the vertical datum was MLLW. Figure 5 shows the extent of coverage of the aerial imagery. Figure 6 shows the water level at Anchorage NOAA station during September 2002 and during the time the aerial imagery was acquired. The imagery was captured during ebb tide and consequently the tidal flat area along the shoreline, between Cairn Point and Point Woronzof, was partially exposed. The imagery was used to resolve the details of the shoreline within its coverage area. The vegetation line was considered as representative of the shoreline where applicable. In areas with revetment, the intersection of the water line with the exposed toe of the revetment was adopted as the shoreline, as was the case in the port area. Figure 7 shows the imagery and the new grid shoreline in the port vicinity.




Figure 4 Previous ADCIRC-2DDI Grid Shoreline Representation




Figure 5 Extent of Aerial Imagery Coverage Used to Define the More Highly Resolved Shoreline




Figure 6 Water Level During September 2002 at Anchorage NOAA Station




Figure 7 Aerial Imagery and Resolved Shoreline in the Immediate Vicinity of the Port

Also, the coastline of the Nautical Chart 16665 (6th edition of 1997) was used to map the ADCIRC grid boundary. The new resolved shoreline in the port vicinity area is shown in Figure 8.




Figure 8 Resolved Shoreline of New ADCIRC-2DDI Grid

Modify Existing Grid

The existing grid should be modified to match the new shoreline. Therefore, some elements were eliminated and more elements were added to fit the new shoreline. In some areas where new elements were added, new small sections of grid mesh were created and then stitched to the old grid. The vertices' spacing of the new added grids were matched with the old shoreline node spacing to preserve the resolution of the grid in the neighboring areas.

Assign Depth Values to Shoreline

Most depth data are referenced to a tidal datum, and tidal datums change throughout Cook Inlet because of the varying tide range. Tide range predictions at 81 subordinate stations were obtained, during the previous study, by applying certain differences to the daily tide predictions of NOAA stations. Figure 9 shows the locations of the 81 subordinate stations. MHW was calculated as half the sum of spring and

mean tidal range at the 81 stations. The previously created scatter XYZ file of the MHW values was used to assign MHW values to the newly created grid boundary nodes.




Figure 9 Location of 81 Subordinate Stations to Assign Depth Values to Shoreline

Update Depth Data in the Port Vicinity

The port area is very dynamic and the bottom topography can change significantly over a relatively short time. Therefore, bathymetric data collected closest to the simulation time should be incorporated in grid generation (Militello 1998).

The original GEOphysical Data System (GEODAS) bathymetric survey files were used to estimate the depth values at the new grid nodes for the area shown in Figure 10. The area was selected to accommodate the updated tidal flat survey data that were provided by the District. More details of the depth data in the area were obtained by using the original high-resolution survey files. The data are referenced to MLLW.

Depths in two areas in the port vicinity (shown in Figure 11) were also updated. The survey in front of the port was conducted during the dredging season of 2002 (July 29). The survey data to the north of the port consisted of two surveys, one conducted during August 2000 and the other was conducted during December 2000. The projection of the data was Alaska State Plane, Zone 4. The horizontal datum was NAD 83 and the vertical datum was MLLW. Both survey data sets were provided by the District.




Figure 10 Area of Updated Depth Data




Figure 11 Updated Survey Data in the Port Vicinity

Improve Representation of Tidal Flat Elevation

The results of the previous regional modeling study showed the importance of accurately representing the tidal flat elevations. The previous study showed that the model was very sensitive to the change of elevation of the tidelands in the immediate area. Additional data were acquired to improve the quality of the modeling. The tidelands' survey data collected during September 2003 are shown in Figure 12 overlapping the 16665 NOAA Nautical Chart. The data projection was Alaska State Plane, Zone 4. The horizontal datum was NAD 83 and the vertical datum was MLLW. This survey data set was also provided by the District.

The survey data show limited coverage of the tidelands in some areas. The issues associated with interpolating data between widely spaced transects are well known, so contour lines created from the survey data points must be carefully produced. Contour lines were created from the survey scatter points and then contour lines were converted to arcs. The number of vertices per arc was selected according to the complexity of the covered area, with much human intervention. The arcs were smoothed and adjusted manually, by moving the vertices, to fit within the MHW and the MLLW lines, and be locally parallel to those lines. The MHW line was defined as the grid shoreline and the MLLW line was the zero contour defined from the GEODAS scatter data and from the 16665 NOAA Nautical Chart. Then the contours which cover the whole tidal flat area were converted back to scatter points which provided better coverage over the entire flats. The newly created scatter set was interpolated to ADCIRC grid to update the tidelands' elevation.

Referencing Depths to ADCIRC Datums

The GEODAS data, the newly created tidelands scatter data, the port survey data, and the survey data collected north of the port were merged. All depths were referenced to Geographic NAD 83 and to MLLW.

ADCIRC simulations are forced with time series of water level referenced to Mean Sea Level (MSL) and therefore the grid bathymetric data should be referenced to MSL. Since the tidal range varies in the study area, the spring tidal range at the 81 subordinate stations in the study area were used to obtain a grid of conversion factors to adjust survey data from MLLW to MSL datums. To convert the depth data from MLLW to MSL, half the spring tidal range should be added to the depth data. The grid area, where the depth data was updated, was split into five sub areas and the conversion factor for each sub area is shown in Figure 13. The new depth data were referenced to MSL before merging them with the rest of the old ADCIRC-2DDI unchanged depth scatter set. The new depth scatter data were interpolated to the new grid.




Figure 12 Tidal Flat Survey Data




Figure 13 Conversion Factors from MLLW to MSL in the Study Area

Tuning the Depth of Shoreline Grid Nodes

The MHHW at Anchorage NOAA station is about 8.8 m referenced to MLLW. After interpolating the updated bathymetric data to the ADCRIC grid, the elevation of some nodes along the shoreline was higher than the MHHW value. Therefore nodes with elevation of about 8.8 m (MLLW) were considered as the shoreline. Figure 14 shows the shoreline defined as the vegetation line, which was extracted from the aerial imagery; and Figure 15 shows the tuned shoreline after updating the depth data in the area.



Figure 14 Shoreline Before Updating the Depth in the Port Vicinity



Figure 15 Shoreline After Updating the Depth in the Port Vicinity

Increase Grid Resolution

The resolution of the grid was increased in an area near and including the Port, which extended about 3.8 km along the shoreline and extended about 550 m offshore as shown in Figure 16. The resolution in this refined area varies, with some elements having sizes of less than 15 m. Element areas vary greatly over the computational domain, with the ratio of the offshore element to the smallest element in the Anchorage area being 9.8×10^6 . The number of nodes and elements of the upgraded grid were 37,148 and 70,605 respectively.




Figure 16 Refined ADCIRC Grid in the Port Vicinity

Improve Grid Quality

Grid quality was enhanced by improving the alignment of elements in the vicinity of the Port. Also alignment of skewed elements in low-resolution areas was improved to insure smooth flow circulation.